
SIEMENS

Data sheet 6XV1830-0EU10

product type designation	**PROFIBUS FC Standard Cable GP**
product description	Standard bus cable (2 wires), preferred length, not assembled
	PROFIBUS FC Standard Cable, bus cable 2-wire, shielded, special configuration for quick assembly, delivery unit: 1000 m.



product brand name	SIMATIC NET
Technical Product Detail Page	https://i.siemens.com/1P6XV1830-0EU10
suitability for use	Standard cable specially designed for fast, permanent installation
cable designation	02YSY (ST) CY 1x2x0,64/2,55-150 VI KF 40 FR
wire length	1000 m; sold by the meter
electrical data	
attenuation factor per length	
● at 9.6 kHz / maximum	0.0025 dB/m
● at 38.4 kHz / maximum	0.004 dB/m
● at 4 MHz / maximum	0.022 dB/m
● at 16 MHz / maximum	0.042 dB/m
impedance	
● rated value	150 Ω
● at 9.6 kHz	270 Ω
● at 38.4 kHz	185 Ω
● at 3 MHz … 20 MHz	150 Ω
relative symmetrical tolerance	
● of the characteristic impedance at 9.6 kHz	10 %
● of the characteristic impedance at 38.4 kHz	10 %
● of the characteristic impedance at 3 MHz … 20 MHz	10 %
loop resistance per length / maximum	110 mΩ/m
shield resistance per length / maximum	9.5 Ω/km
capacity per length / at 1 kHz	28.5 pF/m
operating voltage	
● RMS value	80 V
mechanical data	
number of electrical cores	2
design of the shield	Overlapped aluminum-clad foil, sheathed in a braided screen of tin-plated copper wires
type of electrical connection / FastConnect	Yes
outer diameter	
● of inner conductor	0.65 mm
● of the wire insulation	2.55 mm
● of the inner sheath of the cable	5.4 mm
● of cable sheath	8 mm
symmetrical tolerance of the outer diameter / of cable sheath	0.4 mm
material	

Subject to change without notice
© Copyright Siemens

● of the wire insulation	polyethylene (PE)
● of the inner sheath of the cable	PVC
● of cable sheath	PVC
color	
● of the insulation of data wires	red/green
● of cable sheath	Violet
bending radius	
● with single bend / minimum permissible	37.5 mm
● with multiple bends / minimum permissible	75 mm
tensile load / maximum	100 N
weight per length	78 kg/km
ambient conditions	
ambient temperature	
● during operation	-40 ... +75 °C
● during storage	-40 ... +75 °C
● during transport	-40 ... +75 °C
● during installation	-40 ... +75 °C
● note	electrical properties measured at 20 °C
fire behavior	flame resistant according to IEC 60332-3-24 (Category C) and UL 1685 (CSA FT 4)
class of burning behaviour / according to EN 13501-6	Eca
chemical resistance	
● to mineral oil	oil resistant according to IEC 60811-2-1 (4 h / 70°C)
● to grease	Conditional resistance
● to water	conditional resistance
radiological resistance / to UV radiation	resistant
product features, product functions, product components / general	
product feature	
● halogen-free	No
● silicon-free	Yes
standards, specifications, approvals	
UL/ETL listing / 300 V Rating	Yes; c(ETL)us, CMG / (ETL)us CL3 / Sun Res
UL/ETL style / 600 V Rating	Yes; cRUus AWM 21694 AWM I A/B 60°C 600V FT2
certificate of suitability	
● EAC approval	Yes
● CE marking	Yes
● UL approval	Yes
● RoHS conformity	Yes
● resistance to air pollution / conformity according to ANSI/ISA-71.04	Yes; G3
Marine classification association	
● American Bureau of Shipping Europe Ltd. (ABS)	No
● French marine classification society (BV)	No
● Det Norske Veritas (DNV)	No
● Germanische Lloyd (GL)	No
● Lloyds Register of Shipping (LRS)	No
● Nippon Kaiji Kyokai (NK)	No
● Polski Rejestr Statkow (PRS)	No
standards, specifications, approvals / Environmental Product Declaration	
Environmental Product Declaration	Yes
global warming potential [CO2 eq]	
● total	0.92 kg
● during manufacturing	0.8 kg
● during operation	0.02 kg
● after end of life	0.1 kg
further information / internet links	
internet link	
● to website: Selection guide for cables and connectors	https://support.industry.siemens.com/cs/ww/en/view/109766358

© Copyright Siemens

● to web page: selection aid TIA Selection Tool	https://www.siemens.com/tstcloud
● to web page: SiePortal	https://sieportal.siemens.com/
● to website: Image database	https://www.automation.siemens.com/bilddb
● to website: CAx-Download-Manager	https://www.siemens.com/cax
● to website: Industry Online Support	https://support.industry.siemens.com

security information

security information	Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement - and continuously maintain - a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under https://www.siemens.com/cert. (V4.7)

Approvals / Certificates

General Product Approval

Manufacturer Declaration | Declaration of Conformity | Fire safety / Physical security

General Product Approval | other | Environment

China RoHS | Declaration of Conformity | Miscellaneous

last modified:	3/10/2026

Subject to change without notice
© Copyright Siemens