SIEMENS

## Data sheet 3RT1056-1AB36

Siemens EcoTech



power contactor, AC-3e/AC-3 185 A, 90 kW / 400 V AC (50-60 Hz) / DC Uc: 23-26 V 3-pole, auxiliary contacts 2 NO + 2 NC drive: conventional main circuit: box terminal control and auxiliary circuit: screw terminal

| | |
|---|---|
| **product brand name** | SIRIUS |
| **product designation** | Power contactor |
| **product type designation** | 3RT1 |
| **General technical data** | |
| **size of contactor** | S6 |
| **product extension** | |
| ● function module for communication | No |
| ● auxiliary switch | Yes |
| **power loss [W] for rated value of the current** | |
| ● at AC in hot operating state | 39 W |
| ● at AC in hot operating state per pole | 13 W |
| ● without load current share typical | 5.2 W |
| **type of calculation of power loss current-dependent** | quadratic |
| **insulation voltage** | |
| ● of main circuit with degree of pollution 3 rated value | 1 000 V |
| ● of auxiliary circuit with degree of pollution 3 rated value | 500 V |
| **surge voltage resistance** | |
| ● of main circuit rated value | 8 kV |
| ● of auxiliary circuit rated value | 6 kV |
| maximum permissible voltage for protective separation between coil and main contacts according to EN 60947-1 | 690 V |
| **shock resistance at rectangular impulse** | |
| ● at AC | 8,5 g / 5 ms, 4,2 g / 10 ms |
| ● at DC | 8,5 g / 5 ms, 4,2 g / 10 ms |
| **shock resistance with sine pulse** | |
| ● at AC | 13,4 g / 5 ms, 6,5 g / 10 ms |
| ● at DC | 13,4 g / 5 ms, 6,5 g / 10 ms |
| **mechanical service life (operating cycles)** | |
| ● of contactor typical | 10 000 000 |
| ● of the contactor with added electronically optimized auxiliary switch block typical | 5 000 000 |
| ● of the contactor with added auxiliary switch block typical | 10 000 000 |
| **reference code according to IEC 81346-2** | Q |
| **Substance Prohibitance (day/month/year)** | 05/01/2012 |
| **SVHC substance name** | Lead CAS-No. 7439-92-1 |
| **Net Weight** | 3.791 kg |


Subject to change without notice
© Copyright Siemens

| | |
|---|---|
| **Ambient conditions** | |
| installation altitude at height above sea level maximum | 2 000 m |
| **ambient temperature** | |
| ● during operation | -25 ... +60 °C |
| ● during storage | -55 ... +80 °C |
| **relative humidity minimum** | 10 % |
| **relative humidity at 55 °C according to IEC 60068-2-30 maximum** | 95 % |
| **Main circuit** | |
| **number of poles for main current circuit** | 3 |
| **number of NO contacts for main contacts** | 3 |
| **number of NC contacts for main contacts** | 0 |
| **operating voltage** | |
| ● at AC-3 rated value maximum | 1 000 V |
| ● at AC-3e rated value maximum | 1 000 V |
| **operational current** | |
| ● at AC-1 at 400 V at ambient temperature 40 °C rated value | 215 A |
| ● at AC-1 | |
| — up to 690 V at ambient temperature 40 °C rated value | 215 A |
| — up to 690 V at ambient temperature 60 °C rated value | 185 A |
| — up to 1000 V at ambient temperature 40 °C rated value | 100 A |
| — up to 1000 V at ambient temperature 60 °C rated value | 100 A |
| ● at AC-3 | |
| — at 400 V rated value | 185 A |
| — at 500 V rated value | 185 A |
| — at 690 V rated value | 170 A |
| — at 1000 V rated value | 65 A |
| ● at AC-3e | |
| — at 400 V rated value | 185 A |
| — at 500 V rated value | 185 A |
| — at 690 V rated value | 170 A |
| — at 1000 V rated value | 65 A |
| ● at AC-4 at 400 V rated value | 160 A |
| ● at AC-5a up to 690 V rated value | 189 A |
| ● at AC-5b up to 400 V rated value | 153 A |
| ● at AC-6a | |
| — up to 230 V for current peak value n=20 rated value | 157 A |
| — up to 400 V for current peak value n=20 rated value | 157 A |
| — up to 500 V for current peak value n=20 rated value | 157 A |
| — up to 690 V for current peak value n=20 rated value | 157 A |
| — up to 1000 V for current peak value n=20 rated value | 65 A |
| ● at AC-6a | |
| — up to 230 V for current peak value n=30 rated value | 105 A |
| — up to 400 V for current peak value n=30 rated value | 105 A |
| — up to 500 V for current peak value n=30 rated value | 105 A |
| — up to 690 V for current peak value n=30 rated value | 105 A |
| — up to 1000 V for current peak value n=30 rated value | 65 A |
| minimum cross-section in main circuit at maximum AC-1 rated value | 95 mm² |
| **operational current for approx. 200000 operating cycles at AC-4** | |
| ● at 400 V rated value | 81 A |
| ● at 690 V rated value | 65 A |
| **operational current** | |
| **● at 1 current path at DC-1** | |


Subject to change without notice
© Copyright Siemens

| | |
|---|---|
| — at 24 V rated value | 160 A |
| — at 60 V rated value | 160 A |
| — at 110 V rated value | 18 A |
| — at 220 V rated value | 3.4 A |
| — at 440 V rated value | 0.8 A |
| — at 600 V rated value | 0.5 A |
| **● with 2 current paths in series at DC-1** | |
| — at 24 V rated value | 160 A |
| — at 60 V rated value | 160 A |
| — at 110 V rated value | 160 A |
| — at 220 V rated value | 20 A |
| — at 440 V rated value | 3.2 A |
| — at 600 V rated value | 1.6 A |
| **● with 3 current paths in series at DC-1** | |
| — at 24 V rated value | 160 A |
| — at 60 V rated value | 160 A |
| — at 110 V rated value | 160 A |
| — at 220 V rated value | 160 A |
| — at 440 V rated value | 11.5 A |
| — at 600 V rated value | 4 A |
| **● at 1 current path at DC-3 at DC-5** | |
| — at 24 V rated value | 160 A |
| — at 60 V rated value | 7.5 A |
| — at 220 V rated value | 0.6 A |
| — at 440 V rated value | 0.17 A |
| — at 600 V rated value | 0.12 A |
| **● with 2 current paths in series at DC-3 at DC-5** | |
| — at 24 V rated value | 160 A |
| — at 60 V rated value | 160 A |
| — at 110 V rated value | 160 A |
| — at 220 V rated value | 2.5 A |
| — at 440 V rated value | 0.65 A |
| — at 600 V rated value | 0.37 A |
| **● with 3 current paths in series at DC-3 at DC-5** | |
| — at 24 V rated value | 160 A |
| — at 60 V rated value | 160 A |
| — at 110 V rated value | 160 A |
| — at 220 V rated value | 160 A |
| — at 440 V rated value | 1.4 A |
| — at 600 V rated value | 0.75 A |
| **operating power** | |
| ● at AC-3 | |
| — at 230 V rated value | 55 kW |
| — at 400 V rated value | 90 kW |
| — at 500 V rated value | 132 kW |
| — at 690 V rated value | 160 kW |
| — at 1000 V rated value | 90 kW |
| ● at AC-3e | |
| — at 230 V rated value | 55 kW |
| — at 400 V rated value | 90 kW |
| — at 500 V rated value | 132 kW |
| — at 690 V rated value | 160 kW |
| — at 1000 V rated value | 90 kW |
| **operating power for approx. 200000 operating cycles at AC-4** | |
| ● at 400 V rated value | 45 kW |
| ● at 690 V rated value | 65 kW |
| **operating apparent power at AC-6a** | |
| ● up to 230 V for current peak value n=20 rated value | 60 kVA |


© Copyright Siemens

| | |
|---|---|
| ● up to 400 V for current peak value n=20 rated value | 100 kVA |
| ● up to 500 V for current peak value n=20 rated value | 130 kVA |
| ● up to 690 V for current peak value n=20 rated value | 180 kVA |
| ● up to 1000 V for current peak value n=20 rated value | 110 kVA |
| **operating apparent power at AC-6a** | |
| ● up to 230 V for current peak value n=30 rated value | 40 kVA |
| ● up to 400 V for current peak value n=30 rated value | 70 kVA |
| ● up to 500 V for current peak value n=30 rated value | 90 kVA |
| ● up to 690 V for current peak value n=30 rated value | 120 kVA |
| ● up to 1000 V for current peak value n=30 rated value | 110 kVA |
| **short-time withstand current in cold operating state up to 40 °C** | |
| ● limited to 1 s switching at zero current maximum | 2 900 A; Use minimum cross-section acc. to AC-1 rated value |
| ● limited to 5 s switching at zero current maximum | 2 084 A; Use minimum cross-section acc. to AC-1 rated value |
| ● limited to 10 s switching at zero current maximum | 1 480 A; Use minimum cross-section acc. to AC-1 rated value |
| ● limited to 30 s switching at zero current maximum | 968 A; Use minimum cross-section acc. to AC-1 rated value |
| ● limited to 60 s switching at zero current maximum | 801 A; Use minimum cross-section acc. to AC-1 rated value |
| **no-load switching frequency** | |
| ● at AC | 2 000 1/h |
| ● at DC | 2 000 1/h |
| **operating frequency** | |
| ● at AC-1 maximum | 800 1/h |
| ● at AC-2 maximum | 300 1/h |
| ● at AC-3 maximum | 750 1/h |
| ● at AC-3e | |
| — maximum | 750 1/h |
| ● at AC-4 maximum | 130 1/h |
| **Control circuit/ Control** | |
| **type of voltage of the control supply voltage** | AC/DC |
| **control supply voltage at AC** | |
| ● at 50 Hz rated value | 23 ... 26 V |
| ● at 60 Hz rated value | 23 ... 26 V |
| **control supply voltage at DC rated value** | 23 ... 26 V |
| **operating range factor control supply voltage rated value of magnet coil at DC** | |
| ● initial value | 0.8 |
| ● full-scale value | 1.1 |
| **operating range factor control supply voltage rated value of magnet coil at AC** | |
| ● at 50 Hz | 0.8 ... 1.1 |
| ● at 60 Hz | 0.8 ... 1.1 |
| **design of the surge suppressor** | with varistor |
| **apparent pick-up power** | |
| **● at minimum rated control supply voltage at AC** | |
| — at 50 Hz | 250 V·A |
| — at 60 Hz | 250 V·A |
| **● at maximum rated control supply voltage at AC** | |
| — at 60 Hz | 300 V·A |
| — at 50 Hz | 300 V·A |
| **apparent pick-up power of magnet coil at AC** | |
| ● at 50 Hz | 300 V·A |
| ● at 60 Hz | 300 V·A |
| **inductive power factor with closing power of the coil** | |
| ● at 50 Hz | 0.9 |
| ● at 60 Hz | 0.9 |
| **apparent holding power** | |
| ● at minimum rated control supply voltage at DC | 4.3 V·A |
| ● at maximum rated control supply voltage at DC | 5.2 V·A |
| **apparent holding power** | |
| **● at minimum rated control supply voltage at AC** | |


© Copyright Siemens

| | |
|---|---|
| — at 50 Hz | 4.8 V·A |
| — at 60 Hz | 4.8 V·A |
| **● at maximum rated control supply voltage at AC** | |
| — at 50 Hz | 5.8 V·A |
| — at 60 Hz | 5.8 V·A |
| **inductive power factor with the holding power of the coil** | |
| ● at 50 Hz | 0.8 |
| ● at 60 Hz | 0.8 |
| **closing power of magnet coil at DC** | 360 W |
| **holding power of magnet coil at DC** | 5.2 W |
| **closing delay** | |
| ● at AC | 20 ... 95 ms |
| ● at DC | 20 ... 95 ms |
| **opening delay** | |
| ● at AC | 40 ... 60 ms |
| ● at DC | 40 ... 60 ms |
| **arcing time** | 10 ... 15 ms |
| **control version of the switch operating mechanism** | Standard A1 - A2 |
| **Auxiliary circuit** | |
| number of NC contacts for auxiliary contacts instantaneous contact | 2 |
| number of NO contacts for auxiliary contacts instantaneous contact | 2 |
| operational current at AC-12 maximum | 10 A |
| **operational current at AC-15** | |
| ● at 230 V rated value | 6 A |
| ● at 400 V rated value | 3 A |
| ● at 500 V rated value | 2 A |
| ● at 690 V rated value | 1 A |
| **operational current at DC-12** | |
| ● at 24 V rated value | 10 A |
| ● at 48 V rated value | 6 A |
| ● at 60 V rated value | 6 A |
| ● at 110 V rated value | 3 A |
| ● at 125 V rated value | 2 A |
| ● at 220 V rated value | 1 A |
| ● at 600 V rated value | 0.15 A |
| **operational current at DC-13** | |
| ● at 24 V rated value | 10 A |
| ● at 48 V rated value | 2 A |
| ● at 60 V rated value | 2 A |
| ● at 110 V rated value | 1 A |
| ● at 125 V rated value | 0.9 A |
| ● at 220 V rated value | 0.3 A |
| ● at 600 V rated value | 0.1 A |
| **contact reliability of auxiliary contacts** | 1 faulty switching per 100 million (17 V, 1 mA) |
| **UL/CSA ratings** | |
| **full-load current (FLA) for 3-phase AC motor** | |
| ● at 480 V rated value | 180 A |
| ● at 600 V rated value | 192 A |
| **yielded mechanical performance [hp]** | |
| ● for single-phase AC motor | |
| — at 230 V rated value | 30 hp |
| ● for 3-phase AC motor | |
| — at 200/208 V rated value | 60 hp |
| — at 220/230 V rated value | 75 hp |
| — at 460/480 V rated value | 150 hp |
| — at 575/600 V rated value | 200 hp |
| **contact rating of auxiliary contacts according to UL** | A600 / Q600 |


Subject to change without notice
© Copyright Siemens

| | |
|---|---|
| **Short-circuit protection** | |
| design of the miniature circuit breaker for short-circuit protection of the auxiliary circuit up to 230 V | C characteristic: 10 A; 0.4 kA |
| **design of the fuse link** | |
| ● for short-circuit protection of the main circuit | |
| — with type of coordination 1 required | gG: 355 A (690 V, 100 kA) |
| — with type of coordination 2 required | gG: 315 A (690 V, 100 kA), aM: 200 A (690 V, 50 kA), BS88: 315 A (415 V, 50 kA) |
| ● for short-circuit protection of the auxiliary switch required | gG: 10 A (500 V, 1 kA) |
| **Installation/ mounting/ dimensions** | |
| **mounting position** | with vertical mounting surface +/-90° rotatable, with vertical mounting surface +/- 22.5° tiltable to the front and back |
| fastening method side-by-side mounting | Yes |
| **fastening method** | screw fixing |
| **height** | 172 mm |
| **width** | 120 mm |
| **depth** | 170 mm |
| **required spacing** | |
| ● with side-by-side mounting | |
| — forwards | 20 mm |
| — upwards | 10 mm |
| — downwards | 10 mm |
| — at the side | 0 mm |
| ● for grounded parts | |
| — forwards | 20 mm |
| — upwards | 10 mm |
| — at the side | 10 mm |
| — downwards | 10 mm |
| ● for live parts | |
| — forwards | 20 mm |
| — upwards | 10 mm |
| — downwards | 10 mm |
| — at the side | 10 mm |
| **Connections/ Terminals** | |
| **type of electrical connection** | |
| ● for main current circuit | box terminal |
| ● for auxiliary and control circuit | screw-type terminals |
| ● at contactor for auxiliary contacts | Screw-type terminals |
| ● of magnet coil | screw terminal |
| **type of connectable conductor cross-sections** | |
| ● for main contacts | |
| — stranded | max. 1x 95, 1x 120 mm² |
| — solid or stranded | max. 1x 50, 1x 70 mm² |
| — finely stranded with core end processing | max. 1x 95, 1x 120 mm² |
| — finely stranded without core end processing | max. 1x 95, 1x 120 mm² |
| ● for AWG cables for main contacts | 2x 1/0 |
| **connectable conductor cross-section for main contacts** | |
| ● stranded | 16 ... 70 mm² |
| ● finely stranded with core end processing | 16 ... 70 mm² |
| ● finely stranded without core end processing | 16 ... 70 mm² |
| **connectable conductor cross-section for auxiliary contacts** | |
| ● solid or stranded | 0.5 ... 4 mm² |
| ● finely stranded with core end processing | 0.5 ... 2.5 mm² |
| **type of connectable conductor cross-sections** | |
| ● for auxiliary contacts | |
| — solid | 2x (0.5 ... 1.5 mm²), 2x (0.75 ... 2.5 mm²), max. 2x (0.75 ... 4 mm²) |
| — solid or stranded | 2x (0,5 ... 1,5 mm²), 2x (0,75 ... 2,5 mm²), max. 2x (0,75 ... 4 mm²) |
| — finely stranded with core end processing | 2x (0.5 ... 1.5 mm²), 2x (0.75 ... 2.5 mm²) |
| ● for AWG cables for auxiliary contacts | 2x (20 ... 16), 2x (18 ... 14), 1x 12 |
| **AWG number as coded connectable conductor cross** | 18 ... 14 |


© Copyright Siemens

| | |
|---|---|
| **section for auxiliary contacts** | |
| **Safety related data** | |
| **product function** | |
| **• mirror contact according to IEC 60947-4-1** | Yes |
| **• positively driven operation according to IEC 60947-5-1** | No |
| **• suitable for safety function** | Yes |
| **suitability for use safety-related switching OFF** | Yes |
| **service life maximum** | 20 a |
| **test wear-related service life necessary** | Yes |
| **proportion of dangerous failures** | |
| **• with low demand rate according to SN 31920** | 40 % |
| **• with high demand rate according to SN 31920** | 73 % |
| **B10 value with high demand rate according to SN 31920** | 1 000 000 |
| **failure rate [FIT] with low demand rate according to SN 31920** | 100 FIT |
| ISO 13849 | |
| **device type according to ISO 13849-1** | 3 |
| **overdimensioning according to ISO 13849-2 necessary** | Yes |
| IEC 61508 | |
| **safety device type according to IEC 61508-2** | Type A |
| Electrical Safety | |
| **protection class IP on the front according to IEC 60529** | IP20 |
| **touch protection on the front according to IEC 60529** | finger-safe, for vertical contact from the front |
| **Approvals Certificates** | |
| Environmental Product Declaration | |
| • global warming potential [CO2 eq] / during manufacturing | 17 kg |
| • global warming potential [CO2 eq] / during sales | 0.901 kg |
| • global warming potential [CO2 eq] / during operation | 363 kg |
| • global warming potential [CO2 eq] / after end of life | -2.28 kg |
| • global warming potential [CO2 eq] / total | 379 kg |

**Environment**

Environmental Confirmations

**General Product Approval**

**General Product Approval** | **EMV** | **Functional Saftey**

Type Examination Certificate

**Test Certificates**

Special Test Certificate | Type Test Certificates/Test Report

**Maritime application**

**other**

Miscellaneous | Confirmation

**other**

Miscellaneous | Confirmation

Miscellaneous


**Railway**


Special Test Certificate


**Further information**


© Copyright Siemens

**Information on the packaging**
https://support.industry.siemens.com/cs/ww/en/view/109813875
**Information for data generation and storage**
https://support.industry.siemens.com/cs/ww/en/view/109995012
**Information- and Downloadcenter (Catalogs, Brochures,…)**
https://www.siemens.com/ic10
**Industry Mall (Online ordering system)**
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RT1056-1AB36
**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**
https://support.industry.siemens.com/cs/ww/en/ps/3RT1056-1AB36
**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)**
https://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RT1056-1AB36&lang=en
**Cax online generator**
https://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RT1056-1AB36
**Kennlinien**
https://curves.simaris.siemens.com/curves/3RT1056-1AB36










Subject to change without notice
© Copyright Siemens




**last modified:** 7/22/2026


Subject to change without notice
© Copyright Siemens