SIEMENS

Data sheet 6AV7676-1AC00-0AA0

SIMATIC IPC MD-34A Desk Dock accessories; MD-34A all configurations; 1x LAN 10/100 Mbps, 2x USB 2.0; 1x RS-232; 1x VGA, DC-in 19 V side; 2x USB 2.0; use the MD-34A power supply cord for the Desk Dock



General information	
Design of the programming device	Mobile computer
Supply voltage	
Rated value (DC)	19 V
permissible range, lower limit (AC)	100 V
permissible range, upper limit (AC)	240 V
Interfaces	
Number of RS 232 interfaces	1
Number of USB interfaces	4
● Type A	4; 2* USB 2.0 in rear I/O 2* USB 2.0 in the side I/O
Video interfaces	
● analog video signal (VGA)	Yes
Industrial Ethernet	
● Industrial Ethernet interface	
— 100 Mbps	Yes; 1* 10/100 MBits/s
● Wake on LAN	No
● IAMT (Intel Active Management Technology)	No
Standards, approvals, certificates	
CE mark	Yes
Ambient conditions	
Ambient temperature during operation	
● min.	0 °C
● max.	45 °C
Ambient temperature during storage/transportation	
● min.	-20 °C
● max.	60 °C
Relative humidity	
● Operation, min.	50 %
● Operation, max.	95 %
Dimensions	
Width	292 mm
Height	133 mm
Depth	99 mm
Weights	
Weight, approx.	770 mg
Classifications	

	Version	Classification
eClass	16	27-33-02-92

Subject to change without notice
© Copyright Siemens

eClass	14	27-33-02-92
eClass	12	27-33-02-92
eClass	9.1	27-33-02-92
eClass	9	27-33-02-92
eClass	8	27-24-92-03
eClass	7.1	27-24-92-03
eClass	6	27-24-92-03
ETIM	10	EC002584
ETIM	9	EC002584
ETIM	8	EC002584
ETIM	7	EC002584

Approvals / Certificates

General Product Approval

Manufacturer Declaration

China RoHS

last modified: 6/13/2026

Subject to change without notice
© Copyright Siemens