SIEMENS

Data sheet for SIMOTICS S-1FT7



Figure similar

Article No. : 1FT7105-5AB70-1BA2

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data	
Rated speed	1,500 rpm
Number of poles	10
Rated torque (100 K)	42.0 Nm
Rated current	13.00 A
Static torque (60 K)	41.0 Nm
Static torque (100 K)	50.0 Nm
Stall current (60 K)	12.00 A
Stall current (100 K)	15.00 A
Rotor moment of inertia	178.00 kgcm²
Efficiency	93.0 %

Physical constants	
Torque constant	3.33 Nm/A
Voltage constant at 20° C	214.0 V/1000*min^{-1}
Winding resistance at 20° C	0.26 Ω
Rotary field inductance	6.8 mH
Electrical time constant	27.00 ms
Mechanical time constant	1.20 ms
Thermal time constant	80 min
Shaft torsional stiffness	146,000 Nm/rad
Net weight of the motor	44.2 kg

Mechanical data	
Motor type	Permanent-magnet synchronous motor
Motor type	Compact
Shaft height	100
Cooling	Natural cooling
Radial runout tolerance	0.050 mm
Concentricity tolerance	0.100 mm
Axial runout tolerance	0.100 mm
Vibration severity grade	Grade A
Degree of protection	IP67
Design acc. to Code I	IM B5 (new flange design)
Temperature monitoring	Pt1000 temperature sensor
Color of the housing	Standard (pearl dark gray similar to RAL 9023)
Shaft end type	Fitted key and keyway
Sensor design	Encoder AS24DQI: Absolut encoder Singleturn 24 bit - with signal connection RJ45
Safety Integrated - Suitable encoder	Yes
Electrical connection	Connector turnable
Connector size	1.5

Optimum operating point	
Optimum speed	1,500 rpm
Optimum power	6.6 kW

Limiting data	
Max. permissible speed (mech.)	6,000 rpm
Max. permissible speed (inverter)	2,670 rpm
Maximum torque	200.0 Nm
Maximum current	67.00 A

Recommended Motor Module	
Rated inverter current	18.00 A
Maximum inverter current	54.00 A
Maximum torque	165.0 Nm

Subject to change. Calculated values may differ from nameplate ratings. © Copyright Siemens