SIEMENS

Data sheet 3VL3110-1PE30-0AA0



circuit breaker VL250 UL; type FG (cat no. NFX3T100) non-interchangeable frame, with circuit breaker approval acc. to UL 489 standard breaking capacity 3-pole, NEMA rating 35kA/480V, (molded case circuit breaker) Electronic Trip Unit ETU, LSI TA=40°C In=< 100A, rated current ISD=1.5 to 10xIR, II=11xIN short-circuit protection IR=40-100A Electronic Trip Unit for line protection without connection accessories without auxiliary release without auxiliary/alarm switch, spare part product only for replacement purposes

Weight	2.5 kg
Net Weight	2.5 kg


Approvals / Certificates

Environment		General Product Approval			
Environmental Confirmations	Environmental Confirmations	EAC	Confirmation	CCC	UKCA

Test Certificates	other				Dangerous goods
Special Test Certificate	Miscellaneous	Confirmation	产品合格 QC PASS	Miscellaneous	Transport Information

Further information

Information on the packaging
https://support.industry.siemens.com/cs/ww/en/view/109813875
Information for data generation and storage
https://support.industry.siemens.com/cs/ww/en/view/109995012
Information- and Downloadcenter (catalogues, leaflets,...)
https://www.siemens.com/energy-automation
Industry Mall (Online ordering system)
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VL3110-1PE30-0AA0
Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
https://support.industry.siemens.com/cs/ww/en/ps/3VL3110-1PE30-0AA0
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)
https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VL3110-1PE30-0AA0
CAx-Online-Generator
https://www.siemens.com/cax
Kennlinien
https://curves.simaris.siemens.com/curves/3VL3110-1PE30-0AA0





last modified: 11/24/2025

Subject to change without notice
© Copyright Siemens

Subject to change without notice
© Copyright Siemens