SIEMENS

Data sheet 6DL1134-6TB00-0HX1



Figure similar

SIMATIC ET 200SP HA, ET 200SP, analog ex-i HART input module, Ex-AI 2xI 2-Wire HART, suitable for BaseUnit type X1, channel diagnostics, 16bit, +/-0.3%

General information	
Product type designation	Ex-AI 2xI 2-wire HART
Firmware version	V1.0
● FW update possible	Yes
usable BaseUnits	BU type X1
Product function	
● I&M data	Yes; I&M0 to I&M3
● Isochronous mode	No
Engineering with	
● STEP 7 TIA Portal configurable/integrated from version	V16
● STEP 7 configurable/integrated from version	V5.6 SP2
● PCS 7 configurable/integrated from version	V9.1
● PCS neo can be configured/integrated from version	V3.1
● PROFINET from GSD version/GSD revision	GSDML V2.35
Operating mode	
● MSI	Yes
Redundancy	
● Redundancy capability	No
CiR - Configuration in RUN	
Reparameterization possible in RUN	Yes
Input current	
Current consumption (rated value)	74 mA
Current consumption, max.	92 mA; Peak load (all channels in short-circuit)
Encoder supply	
24 V encoder supply	
● 24 V	Yes
● Short-circuit protection	Yes; Electronic disconnection in case of short-circuit, current limitation from 27 mA
● Output current per channel, max.	28 mA
Power loss	
Power loss, typ.	1.2 W
Address area	
Address space per module	
● Address space per module, max.	4 byte; + 0/1 byte for QI information
● Address space per module with HART, max.	24 byte; + 0/1 byte for QI information
● Address space per module with MultiHART, max.	11 byte; + 0/1 byte for QI information
Hardware configuration	
Automatic encoding	

Subject to change without notice
© Copyright Siemens

● Mechanical coding element	Yes
Selection of BaseUnit for connection variants	
● 2-wire connection	BU type X1
Analog inputs	
Number of analog inputs	2; Differential inputs
● For current measurement	2
Cycle time (all channels), min.	3 ms
Input ranges (rated values), currents	
● 0 to 20 mA	Yes
● 4 mA to 20 mA	Yes; 15 bit + sign
— Input resistance (4 mA to 20 mA)	400 Ω; At 20 mA input current
Cable length	
● shielded, max.	500 m; Ex characteristic values must be observed
● unshielded, max.	300 m; Ex characteristic values must be observed
Analog value generation for the inputs	
Measurement principle	integrating (Sigma-Delta)
Integration and conversion time/resolution per channel	
● Resolution with overrange (bit including sign), max.	16 bit
● Integration time, parameterizable	Yes; channel by channel
● Interference voltage suppression for interference frequency f1 in Hz	10 / 50 / 60 Hz
Smoothing of measured values	
● Number of smoothing levels	4; None; 4/8/16 times
● parameterizable	Yes
Encoder	
Connection of signal encoders	
● for current measurement as 2-wire transducer	Yes
— Burden of 2-wire transmitter, max.	750 Ω; At 20 mA input current
Errors/accuracies	
Linearity error (relative to input range), (+/-)	0.01 %
Temperature error (relative to input range), (+/-)	0.005 %/K
Crosstalk between the inputs, min.	60 dB
Repeat accuracy in steady state at 25 °C (relative to input range), (+/-)	0.05 %
Operational error limit in overall temperature range	
● Current, relative to input range, (+/-)	0.3 %
Basic error limit (operational limit at 25 °C)	
● Current, relative to input range, (+/-)	0.2 %
Interference voltage suppression for f = n x (f1 +/- 1 %), f1 = interference frequency	
● Series mode interference (peak value of interference < rated value of input range), min.	60 dB
Protocols	
HART protocol	Yes
Interrupts/diagnostics/status information	
Diagnostics function	Yes
Alarms	
● Diagnostic alarm	Yes
● Limit value alarm	Yes
Diagnoses	
● Monitoring the supply voltage	Yes
● Wire break	Yes; channel by channel
● Short-circuit	Yes; channel by channel
● Group error	Yes
● Overflow/Underflow	Yes; channel by channel
Diagnostics indication LED	
● MAINT LED	Yes; Yellow LED
● Monitoring of the supply voltage (PWR-LED)	Yes; green PWR LED
● Channel status display	Yes; green LED
● for channel diagnostics	Yes; red LED

Subject to change without notice
© Copyright Siemens

● for module diagnostics	Yes; green/red DIAG LED
Ex(i) characteristics	
maximum values for connecting terminals for gas group IIC	
● Uo (no-load voltage), max.	26 V
● Io (short-circuit current), max.	93 mA
● Po (power output), max.	605 mW
● Co (permissible external capacity), max.	99 nF
● Lo (permissible external inductivity), max.	4 mH
● Ui (intrinsically safe input voltage), max.	10 V
● Um (voltage at non-intrinsically safe connecting terminals), max.	60 V
Potential separation	
Potential separation channels	
● between the channels	No
● between the channels and backplane bus	Yes
● between the channels and the power supply of the electronics	Yes; Electrical isolation between the channels and input voltage PME
Isolation	
Isolation tested with	further information on insulation can be found in the "ET 200SP HA / ET 200SP modules for devices in hazardous areas" System Manual
insulation of the field circuits to local ground acc. to IEC/EN 60079-11 tested with	707 V DC (type test)
Ambient conditions	
Ambient temperature during operation	
● horizontal installation, min.	-40 °C
● horizontal installation, max.	70 °C
● vertical installation, min.	-40 °C
● vertical installation, max.	60 °C
Altitude during operation relating to sea level	
● Installation altitude above sea level, max.	2 000 m
Dimensions	
Width	20 mm
Height	73 mm
Depth	58 mm
Weights	
Weight, approx.	55 g
Classifications	

	Version	Classification
eClass	16	27-24-26-01
eClass	14	27-24-26-01
eClass	12	27-24-26-01
eClass	9.1	27-24-26-01
eClass	9	27-24-26-01
eClass	8	27-24-26-01
eClass	7.1	27-24-26-01
eClass	6	27-24-26-01
ETIM	10	EC001596
ETIM	9	EC001596
ETIM	8	EC001596
ETIM	7	EC001596

Approvals / Certificates

General Product Approval

© Copyright Siemens

General Product Approval	For use in hazardous locations				
Manufacturer Declaration	CCC	UL	INMETRO	Miscellaneous	ATEX

For use in hazardous locations	Maritime application				
IECEx	ABS	BUREAU VERITAS	DNV	LRS	NK / Nippon Kaiji Kyokai

Maritime application		Environment
RINA	CCS (China Classification Society)	EPD

last modified: 10/23/2025

Subject to change without notice
© Copyright Siemens