SIEMENS

Data sheet 3RT2637-1AF05

capacitor contactor, AC-6b 75 kVAr, / 400 V, 3-pole, 110 V AC, 50 Hz, auxiliary contacts: 2 NC, screw terminal, size: S2

product brand name	SIRIUS
product designation	capacitor contactors
product type designation	3RT26
General technical data	
size of contactor	S2
product extension auxiliary switch	Yes
power loss [W] for rated value of the current	
● at AC in hot operating state per pole	3.8 W
● without load current share typical	6 W
type of calculation of power loss current-dependent	quadratic
insulation voltage	
● of main circuit with degree of pollution 3 rated value	690 V
● of auxiliary circuit with degree of pollution 3 rated value	690 V
surge voltage resistance	
● of main circuit rated value	6 kV
● of auxiliary circuit rated value	6 kV
maximum permissible voltage for protective separation between coil and main contacts according to EN 60947-1	400 V
shock resistance at rectangular impulse	
● at AC	6.8 g / 5 ms, 4 g / 10 ms
shock resistance with sine pulse	
● at AC	10.6 g / 5 ms, 6.2 g / 10 ms
mechanical service life (operating cycles)	
● of the contactor with added auxiliary switch block typical	3 000 000
electrical endurance (operating cycles)	150 000
reference code according to IEC 81346-2	Q
Substance Prohibitance (day/month/year)	05/01/2014
Net Weight	1.006 kg
Ambient conditions	
installation altitude at height above sea level maximum	2 000 m
ambient temperature	
● during operation	-25 ... +60 °C
● during storage	-55 ... +80 °C
relative humidity minimum	10 %
relative humidity at 55 °C according to IEC 60068-2-30 maximum	95 %
Main circuit	
number of poles for main current circuit	3
number of NO contacts for main contacts	3

Subject to change without notice
© Copyright Siemens

number of NC contacts for main contacts	0
operational current at AC-6b at 690 V at ambient temperature 60 °C rated value	108 A
operating reactive power at AC-6b	
● at 230 V at 50/60 Hz at ambient temperature 60 °C rated value	14 ... 43 kvar
● at 400 V at 50/60 Hz at ambient temperature 60 °C rated value	25 ... 75 kvar
● at 500 V at 50/60 Hz at ambient temperature 60 °C rated value	31 ... 94 kvar
● at 690 V at 50/60 Hz at ambient temperature 60 °C rated value	43 ... 129 kvar
no-load switching frequency	
● at AC	500 1/h
operating frequency at AC-6b	
● at 230 V maximum	100 1/h
● at 240 V maximum	100 1/h
● at 400 V maximum	100 1/h
● at 480 V maximum	50 1/h
● at 500 V maximum	45 1/h
● at 600 V maximum	32 1/h
● at 690 V maximum	25 1/h
Control circuit/ Control	
type of voltage	AC
type of voltage of the control supply voltage	AC
control supply voltage at AC	
● at 50 Hz rated value	110 V
control supply voltage frequency	
● 1 rated value	50 Hz
operating range factor control supply voltage rated value of magnet coil at AC	
● at 50 Hz	0.8 ... 1.1
apparent pick-up power of magnet coil at AC	190 V·A
inductive power factor with closing power of the coil	0.72
apparent holding power of magnet coil at AC	16 V·A
inductive power factor with the holding power of the coil	0.37
closing delay	
● at AC	10 ... 80 ms
opening delay	
● at AC	10 ... 18 ms
arcing time	10 ... 20 ms
control version of the switch operating mechanism	Standard A1 - A2
Auxiliary circuit	
number of NC contacts for auxiliary contacts	2
● attachable	1
● instantaneous contact	2
number of NO contacts for auxiliary contacts	0
● attachable	1
● instantaneous contact	0
operational current of auxiliary contacts at AC-12 maximum	10 A
operational current of auxiliary contacts at AC-15	
● at 230 V	6 A
● at 400 V	3 A
● at 690 V	0 A
operational current of auxiliary contacts at DC-13	
● at 24 V	6 A
● at 60 V	2 A
● at 110 V	1 A
● at 125 V	0.9 A
● at 220 V	0.3 A
contact reliability of auxiliary contacts	0.00000001

© Copyright Siemens

UL/CSA ratings	
contact rating of auxiliary contacts according to UL	A600 / Q600
Short-circuit protection	
design of the miniature circuit breaker for short-circuit protection of the auxiliary circuit up to 230 V	C characteristic: 10 A; 0.4 kA
design of the fuse link	
● for short-circuit protection of the main circuit with type of coordination 1 required	gG: 200 A (690 V, 50 kA)
● for short-circuit protection of the auxiliary switch required	gG: 10 A (690 V, 1 kA)
Installation/ mounting/ dimensions	
mounting position	+/-180° rotation possible on vertical mounting surface; can be tilted forward and backward by +/- 22.5° on vertical mounting surface
fastening method	screw and snap-on mounting onto 35 mm DIN rail according to DIN EN 50022
height	114 mm
width	65 mm
depth	130 mm
required spacing	
● with side-by-side mounting at the side	10 mm
● for grounded parts at the side	10 mm
Connections/ Terminals	
type of electrical connection	
● for main current circuit	screw-type terminals
● for auxiliary and control circuit	screw-type terminals
● at contactor for auxiliary contacts	Screw-type terminals
● of magnet coil	screw terminal
type of connectable conductor cross-sections for main contacts	
● solid	2x (1 ... 16 mm²)
● stranded	2x (10 ... 35 mm²), 1x (10 ... 50 mm²)
● solid or stranded	2x (1 ... 35 mm²), 1x (1 ... 50 mm²)
● finely stranded with core end processing	2x (1 ... 25 mm²), 1x (1 ... 35 mm²)
type of connectable conductor cross-sections	
● for auxiliary contacts	
— solid	2x (0.5 ... 1.5 mm²), 2x (0.75 ... 2.5 mm²), 2x 4 mm²
— solid or stranded	2x (0.5 ... 1.5 mm²), 2x (0.75 ... 2.5 mm²), 2x 4 mm²
— finely stranded with core end processing	2x (0.5 ... 1.5 mm²), 2x (0.75 ... 2.5 mm²)
● for AWG cables for auxiliary contacts	2x (20 ... 16), 2x (18 ... 14), 2x 12
type of minimum connectable cross-sections for main contacts at AC-6b	
● at 40 °C	1x 50 mm²
● at 60 °C	2x 35 mm²
AWG number as coded connectable conductor cross section for main contacts	18 ... 0
Safety related data	
product function	
● **mirror contact according to IEC 60947-4-1**	No
● **positively driven operation according to IEC 60947-5-1**	No
Electrical Safety	
protection class IP on the front according to IEC 60529	IP20
touch protection on the front according to IEC 60529	finger-safe, for vertical contact from the front
Approvals Certificates	
Environmental Product Declaration	
● global warming potential [CO2 eq] / during manufacturing	2.47 kg
● global warming potential [CO2 eq] / during operation	104 kg
● global warming potential [CO2 eq] / after end of life	-0.226 kg
● global warming potential [CO2 eq] / total	106 kg
Environment	**General Product Approval**

© Copyright Siemens

Environmental Confirmations

General Product Approval	EMV	Test Certificates	Maritime application
		Type Test Certificates/Test Report	

other	Dangerous goods
Confirmation	Transport Information

Further information

Information on the packaging
https://support.industry.siemens.com/cs/ww/en/view/109813875
Information for data generation and storage
https://support.industry.siemens.com/cs/ww/en/view/109995012
Information- and Downloadcenter (Catalogs, Brochures,…)
https://www.siemens.com/ic10
Industry Mall (Online ordering system)
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RT2637-1AF05
Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
https://support.industry.siemens.com/cs/ww/en/ps/3RT2637-1AF05
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)
https://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RT2637-1AF05&lang=en
Cax online generator
https://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RT2637-1AF05
Kennlinien
https://curves.simaris.siemens.com/curves/3RT2637-1AF05

© Copyright Siemens





last modified: 7/22/2026

Subject to change without notice
© Copyright Siemens

Subject to change without notice
© Copyright Siemens