SIEMENS

Data sheet 6GT2002-0ED00

product type designation	**ASM 456 communication module**
	- - spare part - - MOBY communications module ASM456 for PROFIBUS DP-V1; 2 read-write devices can be connected; without connection block for PROFIBUS.



product brand name	SIMATIC RF
suitability for operation	PROFIBUS network according to DP-V1 together with RF200/300/600, MV400/500, MOBY D/E/I/U
transfer rate	
transfer rate / with PROFIBUS	9.6 kbit/s ... 12 Mbit/s
transfer rate / at the point-to-point connection / serial / maximum	115.2 kbit/s
interfaces	
design of the interface / for point-to-point connection	RS422
number of readers / connectable	2
type of electrical connection	
● of the PROFIBUS interface	(according to the connection block)
● for supply voltage	(according to the connection block)
design of the interface / to the reader / for communication	M12, 8-pin
mechanical data	
material	Thermoplastic (Valox 467, fiberglass reinforced)
color	IP Basic 714
tightening torque / of the screw for securing the equipment / maximum	3 N·m
supply voltage, current consumption, power loss	
supply voltage / at DC	
● rated value	24 V
●	20 ... 30 V
consumed current	
● at DC / at 24 V / without connected devices / typical	0.08 A
● from supply voltage 1L+ / maximum	0.85 A
ambient conditions	
ambient temperature	
● during operation	0 ... 55 °C
● during storage	-40 ... +70 °C
● during transport	-40 ... +70 °C
protection class IP	IP67
shock resistance	According to IEC 61131-2
shock acceleration	300 m/s²
vibrational acceleration	100 m/s²
design, dimensions and weights	
width	60 mm
height	30 mm
depth	210 mm

Subject to change without notice
© Copyright Siemens

net weight	0.21 kg
fastening method	2 x M5 screws
wire length / for RS 422 interface / maximum	1000 m
product features, product functions, product components / general	
display version	4 LEDs per reader connection, 4 LEDs for device status
product function / addressable transponder file handler	Yes
protocol / is supported	
● PROFIBUS DP-V0 protocol	No
● PROFIBUS DP-V1 protocol	Yes
product functions / management, configuration, engineering	
type of parameterization	GSD
type of programming	FB 45, FB 55, FC 56, ID profile, library with functions, (FC 45/55 with restricted functionality)
type of computer-switched communication	acyclic communication
standards, specifications, approvals	
certificate of suitability	CE, FCC, cULus
MTBF	122 a
accessories	
accessories	Connection block for ECOFAST system or M12, 7/8"
further information / internet links	
internet link	
● to web page: selection aid TIA Selection Tool	https://www.siemens.com/tstcloud
● to website: Image database	https://www.automation.siemens.com/bilddb
● to website: CAx-Download-Manager	https://www.siemens.com/cax
● to website: Industry Online Support	https://support.industry.siemens.com
security information	
security information	Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement - and continuously maintain - a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under https://www.siemens.com/cert. (V4.7)

Approvals / Certificates

General Product Approval

Declaration of Conformity | China RoHS | Manufacturer Declaration

General Product Approval	EMV	Environment	Industrial Communication
Miscellaneous			PROFINET

last modified: 3/10/2026

Subject to change without notice
© Copyright Siemens