SIEMENS

Data sheet 7XV5103-0AA10

Y-Bus cable for RS485 bus connection of protection device with 9-pin plug (D-sub) or extension of bus, 2-core, screened, length: x m; not suitable for Profibus! x = 1, 3, 5, 10



Figure similar

General technical data	
AWG number	30
Model	
product designation	RS485 bus cable system 7XV5103
Mechanical Design	
length	10 m
type of plug connector / 1	D-sub connector plug, 9-pole
type of plug connector / 2	D-sub socket, 9-pole
type of plug connector	D-sub (9-pole)
color / of cable sheath	gray/white
design of the anti-kink sleeve	metalized, shielded connector housings with reduced flush mounting depth and strain relief
cable design	twisted pairs, shielded (STP)
contact assignment	3, 8
Further information	

Siemens is working on the renewal of the current EAC certificates.
Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).

Information- and Downloadcenter (catalogues, leaflets,...)
https://www.siemens.com/energy-automation

Industry Mall (Online ordering system)
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=7XV5103-0AA10

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
https://support.industry.siemens.com/cs/ww/en/ps/7XV5103-0AA10

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)
https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=7XV5103-0AA10

Tender specifications
https://www.siemens.com/specifications

Power Academy - Your training and consulting partner in the area of power transmission and distribution
https://www.siemens.com/poweracademy

Subject to change without notice
© Copyright Siemens