

PANEL5000-A122

Precision resistive touch screen, COM / USB optional, VGA / DVI signal input

Industrial Touch Monitor



Introduction

PANEL5000-A122 is ultra-thin industrial touch monitor that supports VGA and DVI inputs, front panel made of magnesium alloy with a PET film, support 12-24V DC power input, power interface uses Fastening Type Phoenix terminal, to prevent accidental removal during use; touch screen with high temperature five-wire resistive, with high sensitivity, dust and waterproof, anti-oil, with gloves may merit normal operation, touch screen flexibility to choose the COM port, USB port to communicate with the host.

PANEL5000-A122 front panel compliant NEMA / IP65 waterproof and dustproof standard, to prevent installation in the control cabinet because of the scene splashing water droplets and water vapor into the host and thus affect equipment operation; high-strength steel box structure, so that it can adapt to the harsh industrial site work environment, the most suitable for factory automation, machinery manufacturing, CNC equipment, textile equipment, communication networks, power automation and other industrial applications.

Features and Benefits



Using precision resistive touch screen



Rugged steel structure



Phoenix terminal using fastening type power connector




Supports VESA wall mount



OSD control buttons on the rear panel

Specifications

| Institutional | | LCD | |
|-------------------|--|------------------|--------------------------------------|
| Front Panel | Magnesium alloy front panel IP65 degree of protection, steel-type box structure | Size / Type | 12.1-inch TFT LCD |
| Mounting | Embedded panel and VESA wall mounting | Resolution | 1024 x 768 |
| Buttons | The back of the machine is equipped with switches, lights, and OSD control buttons | Maximum color | 262K |
| Signal Input | DVI and VGA | Display area | 246 × 184.5mm |
| Communication | COM/USB | Reaction time | 16ms |
| Power Input | 12-24V DC voltage input | Backlit | LED |
| Front Color | Silver (plus PET film) | Backlit MTBF | 30,000 hours |
| Overall size | 321×242.8×50mm(W×H×D) | Lattice | 0.3075×0.3075 |
| Case Size | 301×227×44mm(W×H×D) | Brightness | 300cd/m ² |
| Hole Size | 304×230 mm(W x H) | Contrast ratio | 800:1 |
| Weight | 2.86kg | Max view angle | (H)130/(V)120 |
| Environmental | | Touch screen | |
| Working tem. | -20~+60℃ Electronic disk | Size / Type | 12.1-inch five-wire analog resistive |
| Storage tem. | -30~+80℃ | Resolution | 4096×4096 |
| Relative humidity | 5~95%@40℃ No condensation | Response time | <5ms |
| Vibration | 5~500Hz,1.5G,0.15mm Peak to peak | Surface hardness | 3H |
| Shock | 10G/peak 11ms sec | Click life | 250g efforts, 35 million times |
| | | Stroke life | 250g efforts, 5 million times |
| | | Transmittance | More than 81% |



Ordering Information

| | |
|--------------------|--|
| PANEL5000-A122-TUH | 12.1-inch TFT LCD/Resolution 1024 x 768/VGA/DVI/Resistive Touch Screen/ USB/ DC 12-24V/adapter |
| PANEL5000-A122-TSH | 12.1-inch TFT LCD/Resolution 1024 x 768/VGA/DVI/Resistive Touch Screen/ COM/ DC 12-24V/adapter |
| PANEL5000-A122-CH | 12.1-inch TFT LCD/Resolution 1024 x 768/VGA/DVI/Glass/ DC 12-24V/adapter |

Packing List:

Hook: 8*Hooks apply to Thickness=1mm~1.2mm

Terminal: 2pin Phoenix terminal

VGA Cable: 1.8M

USB Cable: 1.8M

Optional Equipment:

Adapter: 12V/3.33A,40W 2pin Phoenix terminal

Chinese Standard Power Line: 1.8M/3M/5M

VGA Cable: 3M/5M

USB Cable: 3M/5M

DVI Cable: 1.8M/3M/5M