SIEMENS

## Data sheet 6ES7194-2LH10-1AB0

Power cable M8, both ends assembled with M8 connector angled and M8 socket angled, 4-pole, Length 1.0 m



Figure similar

| | |
|---|---|
| **General information** | |
| Product type designation | Power cable |
| Product description | Flexible cable (4-core), preassembled at each end with a 4-pin M8 male / female connector, angled |
| Suitability for use | For connection to ET 200AL for 24 V DC power supply |
| **Degree and class of protection** | |
| IP degree of protection | IP65/67 |
| **Ambient conditions** | |
| Ambient temperature during assembly, min. | -30 °C |
| Ambient temperature during assembly, max. | 80 °C |
| Ambient temperature during storage/transportation | |
| ● min. | -40 °C |
| ● max. | 80 °C |
| **Cables** | |
| Cable designation | 4 Li9Y 0.50 mm² Y |
| Cable length | 1 m |
| Number of electrical cores | 4 |
| Outer diameter of inner conductor | 0.8 mm |
| Outer diameter of core insulation | 1.46 mm |
| Outer diameter of cable sheath | 5.2 mm |
| Number of bending cycles | 2 500 000; cable carrier compliant for 2.5 million bending cycles with a bending radius of 52 mm, a speed of 3 m/s and an acceleration of 10 m/s² |
| Permissible bending radius, single bend, min. | 26 mm |
| Permissible bending radius, multiple bends, min. | 52 mm |
| Bending radius for continuous bending | 52 mm |
| Color of cable sheath | gray |
| Color of core insulation of energy core | white / brown / blue / black |
| Weight per length | 44 kg/km |
| **Mechanics/material** | |
| Outgoing feeder type | 90 degree cable outlet |
| Material of cable sheath | PVC |
| Material of core insulation | PP |
| Material property | |
| ● Silicone-free | Yes |
| **Classifications** | |

| | Version | Classification |
|---|---|---|
| eClass | 16 | 27-24-22-20 |
| eClass | 14 | 27-24-22-20 |


Subject to change without notice
© Copyright Siemens

| | | |
|---|---|---|
| eClass | 12 | 27-24-22-20 |
| eClass | 9.1 | 27-24-22-20 |
| eClass | 9 | 27-24-22-20 |
| eClass | 8 | 27-24-92-05 |
| eClass | 7.1 | 27-24-92-05 |
| eClass | 6 | 27-24-92-05 |
| ETIM | 10 | EC000237 |
| ETIM | 9 | EC000237 |
| ETIM | 8 | EC000237 |
| ETIM | 7 | EC000237 |
| IDEA | 4 | 3553 |
| UNSPSC | 15 | 32-15-17-03 |

## Approvals / Certificates

### General Product Approval

Miscellaneous | Manufacturer Declaration | China RoHS

**last modified:** 4/7/2025


Subject to change without notice
© Copyright Siemens