SIEMENS

Data sheet 4NC5435-2CH21

current transformer 1500/5 A, 10 VA, Cl. 1.0

Model	
product brand name	SENTRON
product designation	Current transformer
design of the product	Bushing-type current transformers
product quality calibrated	No
size of the current transformer	4
operating apparent power rated value	10 V·A
operating voltage	0.72 kV
insulation voltage rated value	3 kV
designation of overcurrent limiting factor	FS 5
operational current rated value maximum	1 800 A
current	
● **at input rated value**	1 500 A
● **at output rated value**	5 A
accuracy class of the current transformer	class 1
value range of the operating frequency	50/60 Hz
Protection class	
protection class IP	IP20
suitability for use for outside use	No
suitability for use for interior use	Yes
product feature touch protection	Yes
Short circuit	
formula for rated short-time thermal current (Ith) for 1 s according to IEC 61869-2	60 x Ipr
formula for rated dynamic current (Idyn) according to IEC 61869-2	2.5 x Ith or 150 x Ipr
Connections	
type of electrical connection at output	screw-type terminals
Mechanical Design	
height	127.5 mm
height of the opening	36 mm
width	112 mm
width of the push-through bus bar	
● at 1 bus bar maximum	64 mm
● in case of 2 bus bars maximum	51 mm
depth	77 mm
fastening method	screw fixing
diameter of inlet opening	41 mm
outer diameter of the push-through conductor maximum	41 mm
Net Weight	1.113 kg
Environmental conditions	
ambient temperature during operation	
● minimum	-30 °C
● maximum	55 °C
ambient temperature during storage	
● minimum	-30 °C
● maximum	70 °C
Approvals Certificates	

Environment	General Product Approval	other

Subject to change without notice
© Copyright Siemens

Environmental Confirmations | Confirmation | Confirmation

other



Further information

Information on the packaging
https://support.industry.siemens.com/cs/ww/en/view/109813875
Information for data generation and storage
https://support.industry.siemens.com/cs/ww/en/view/109995012
Information- and Downloadcenter (Catalogs, Brochures,…)
https://www.siemens.com/lowvoltage/catalogs
Industry Mall (Online ordering system)
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=4NC5435-2CH21
Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
https://support.industry.siemens.com/cs/ww/en/ps/4NC5435-2CH21
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)
https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=4NC5435-2CH21
CAx-Online-Generator
https://www.siemens.com/cax
Tender specifications
https://www.siemens.com/specifications
Kennlinien
https://curves.simaris.siemens.com/curves/4NC5435-2CH21

last modified: 12/10/2025

Subject to change without notice
© Copyright Siemens