

Article No. : 1FL2104-4AF01-0HC0

Client order no. :  
Order no. :  
Offer no. :  
Remarks :

Item no. :  
Consignment no. :  
Project :



| Basic motor data        |                                                     |
|-------------------------|-----------------------------------------------------|
| Motor type              | Permanent-magnet synchronous motor, Natural cooling |
| Motor type              | Low Inertia                                         |
| Static torque           | 3.20 Nm                                             |
| Static current          | 3.00 A                                              |
| Maximum torque          | 10.80 Nm                                            |
| Maximum current         | 10.90 A                                             |
| Maximum speed           | 6,500 rpm                                           |
| Rotor moment of inertia | 0.6300 kgcm <sup>2</sup>                            |
| Weight                  | 3.30 kg                                             |

| Rated data                        |           |
|-----------------------------------|-----------|
| SINAMICS S200, 3 AC 380 ... 480 V |           |
| Rated speed                       | 3,000 rpm |
| Rated torque                      | 3.20 Nm   |
| Rated current                     | 3.00 A    |
| Rated power                       | 1.00 kW   |

| Encoder system |                                    |
|----------------|------------------------------------|
| Encoder system | Absolute encoder singleturn 17 bit |

| Motor connection |                        |
|------------------|------------------------|
| Connection type  | Metal hybrid connector |

| Mechanical data               |                      |
|-------------------------------|----------------------|
| Design acc. to Code I         | IM B5 (IM V1, IM V3) |
| Vibration severity grade      | Grade A              |
| Shaft height                  | 40                   |
| Flange size (AB)              | 81 mm                |
| Centering ring (N)            | 70 mm                |
| Hole circle (M)               | 90 mm                |
| Screw-on hole (S)             | 6.6 mm               |
| Overall length (LB)           | 142.6 mm             |
| Diameter of shaft (D)         | 19 mm                |
| Length of shaft (E)           | 40 mm                |
| Length of flange diagonal (P) | 104.9 mm             |
| Shaft end                     | Plain shaft          |
| Color of the housing          | Anthracite RAL 7016  |

