SIEMENS

Data sheet for SINAMICS G110

Article No. : **6SL3211-0KB15-5BA1**



Figure similar

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Rated data

Input	
Number of phases	AC
Line voltage	... V ± %
Line frequency	... Hz
Rated current	A
Output	
Number of phases	?PMD_AAC041_001_000 ?
Rated power	kW
Rated current (IN)	A
Pulse frequency	kHz
Output frequency for V/f control	... Hz
?PMD_ACF281_001_000 ?	

General tech. specifications

Offset factor cos φ

Communication

Communication	?PMD_ABY317_001_000 ?

Mechanical data

Degree of protection	?PMD_ABJ176_001_000 ?
Frame size	?PMD_ABW171_001_000 ?
Net weight	kg
Width	?PMD_ABJ184_001_000 ? mm
Height	?PMD_ABJ182_001_000 ? mm
Depth	?PMD_ABJ179_001_000 ? mm

Ambient conditions

Installation altitude	m
Ambient temperature	
Operation	... °C
Storage	... °C
Relative humidity	
Max. operation	% ?PMD_ACA712_001_000 ?

Closed-loop control techniques

V/f linear / square-law / parameterizable	?PMD_ABY274_001_000 ?

Standards

Compliance with standards	?PMD_AAA074_001_000 ?
CE marking	?PMD_ABY842_001_000 ?

Inputs / outputs

Digital inputs	
Number	
Digital outputs	
Number	(?PMD_AAC367_001_000 ?)

Subject to change. Calculated values may differ from nameplate ratings. © Copyright Siemens