SIEMENS

Data sheet 6AV6574-1AD00-4EX0



protective film 15" touch devices for MP 370 15" Touch, TP 1500 Basic, MP 377 15" Touch and Thin Client 15", scope of supply: 10 protective films

General information	
Product type designation	Protective film 15", 4:3
Installation type/mounting	
Mounting in portrait format possible	Yes
Mounting in landscape format possible	Yes
Standards, approvals, certificates	
CE mark	Yes
Ambient conditions	
Ambient temperature during operation	
● min.	-40 °C
● max.	50 °C
Ambient temperature during storage/transportation	
● min.	-40 °C
● max.	80 °C
Relative humidity	
● Operation, max.	90 %
Mechanics/material	
Material	
● plastic	Yes; Nonreflecting
Dimensions	
Width	362 mm
Height	289 mm
Thickness	0.125 mm
Scope of supply	
Delivery quantity in pieces	10
Other	
printable with laser printer	Yes
Merchandise	No
Manufacturer name	SIEMENS AG
Manufacturer's address	Gleiwitzerstraße 555, 90475 Nuremberg, Germany
Note:	Not suitable for widescreen
Classifications	

	Version	Classification
eClass	16	27-33-02-92
eClass	14	27-33-02-92
eClass	12	27-33-02-92
eClass	9.1	27-33-02-92

Subject to change without notice
© Copyright Siemens

eClass	9	27-33-02-92
eClass	8	27-24-92-03
eClass	7.1	27-24-92-03
eClass	6	27-24-92-03
ETIM	10	EC002584
ETIM	9	EC002584
ETIM	8	EC002584
ETIM	7	EC002584
IDEA	4	3552
UNSPSC	15	32-15-17-03

Approvals / Certificates

General Product Approval

Manufacturer Declaration

Further information

Usable in the following products: Detailed information can be found in the cross-list, which is available for download in the following SIOS note: 40466415
https://support.industry.siemens.com/cs/document/40466415/status-of-the-simatic-hmi-accessories-and-cross-list-update?dti=0&lc=en-WW

last modified: 9/4/2024

Subject to change without notice
© Copyright Siemens