

## Data sheet for SIMOTICS S-1FL2

Article No. : 1FL2310-2AC11-1HB0

Client order no. :  
Order no. :  
Offer no. :  
Remarks :

Item no. :  
Consignment no. :  
Project :



### Basic motor data

|                         |                                                     |
|-------------------------|-----------------------------------------------------|
| Motor type              | Permanent-magnet synchronous motor, Natural cooling |
| Motor type              | High Inertia                                        |
| Static torque           | 18.10 Nm                                            |
| Static current          | 11.00 A                                             |
| Maximum torque          | 55.00 Nm                                            |
| Maximum current         | 36.20 A                                             |
| Maximum speed           | 3,000 rpm                                           |
| Rotor moment of inertia | 78.4700 kgcm <sup>2</sup>                           |
| Weight                  | 25.40 kg                                            |

### Rated data

SINAMICS S200, 3 AC 380 ... 480 V

|               |           |
|---------------|-----------|
| Rated speed   | 2,000 rpm |
| Rated torque  | 16.70 Nm  |
| Rated current | 11.00 A   |
| Rated power   | 3.50 kW   |

### Encoder system


|                |                                    |
|----------------|------------------------------------|
| Encoder system | Absolute encoder singleturn 17 bit |
|----------------|------------------------------------|

### Motor connection

|                 |                         |
|-----------------|-------------------------|
| Connection type | Metal angular connector |
|-----------------|-------------------------|

### Mechanical data

|                               |                                              |
|-------------------------------|----------------------------------------------|
| Design acc. to Code I         | IM B5 (IM V1, IM V3)                         |
| Vibration severity grade      | Grade A                                      |
| Shaft height                  | 90                                           |
| Flange size (AB)              | 180 mm                                       |
| Centering ring (N)            | 114.3 mm                                     |
| Hole circle (M)               | 200 mm                                       |
| Screw-on hole (S)             | 13.5 mm                                      |
| Overall length (LB)           | 281 mm                                       |
| Diameter of shaft (D)         | 35 mm                                        |
| Length of shaft (E)           | 80 mm                                        |
| Length of flange diagonal (P) | 228 mm                                       |
| Shaft end                     | Shaft with parallel key (half-key balancing) |
| Color of the housing          | Anthracite RAL 7016                          |



### Holding brake

|                          |              |
|--------------------------|--------------|
| Rated voltage            | 24 V DC 10 % |
| Rated current            | 1.90 A       |
| Holding torque $M_{4Br}$ | 30.00 Nm     |
| Opening time             | 220 ms       |
| Closing time             | 115 ms       |