SIEMENS

Data sheet 5SV8704-2KK

Siemens EcoTech

Summation current transformer type B, 210 mm, 300 mA 1A



Model	
product brand name	SENTRON
product designation	summation current transformer
design of the product	Type B
residual current (Idn) minimum	300 mA
internal diameter of summation current transformer	210 mm
symmetrical tolerance of supply voltage at DC	12 V
wire length maximum	10 m
protection class IP at connection all terminals	IP20
apparent power consumption maximum	2.5 V·A
type of voltage of the operating voltage for actuation	AC/DC
surge voltage resistance rated value	8 kV
operating voltage rated value	
• maximum	690 V
Main circuit	
operating frequency rated value	
• minimum	0 Hz
• maximum	2 000 Hz
operational current rated value	630 A
Control current	
control supply voltage	
• at AC at 50 Hz rated value maximum	690 V
• at AC at 60 Hz rated value maximum	690 V
Suitability	
suitability for use	for AC and DC systems
Product function	
product function error memory	No
Connections	
type of connectable conductor cross-sections	6 x 0.75 mm²
type of electrical connection	Plug-in terminal
Mechanical Design	
height	80 mm
width	323 mm
depth	304.5 mm
Net Weight	4.49 kg
Environmental conditions	

Subject to change without notice
© Copyright Siemens

influence of the surrounding temperature	Max. 95% humidity
ambient temperature during operation	
● minimum	-10 °C
● maximum	55 °C
ambient temperature during storage	
● minimum	-10 °C
● maximum	55 °C

Certificates

reference code according to IEC 81346-2	T


Approvals Certificates

Environment			General Product Approval		
Environmental Confirmations	Siemens EcoTech	Environmental Confirmations	EAC	Confirmation	CE EG-Konf.

General Product Approval	other
UK CA	产品合格 QC PASS	Confirmation

Further information

Information on the packaging
https://support.industry.siemens.com/cs/ww/en/view/109813875
Information for data generation and storage
https://support.industry.siemens.com/cs/ww/en/view/109995012
Information- and Downloadcenter (Catalogs, Brochures,…)
https://www.siemens.com/lowvoltage/catalogs
Industry Mall (Online ordering system)
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5SV8704-2KK
Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
https://support.industry.siemens.com/cs/ww/en/ps/5SV8704-2KK
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)
https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SV8704-2KK
CAx-Online-Generator
https://www.siemens.com/cax
Tender specifications
https://www.siemens.com/specifications
Kennlinien
https://curves.simaris.siemens.com/curves/5SV8704-2KK



Type	Dimensions F
5SV8 701-2KK	35
5SV8 701-2KP	35
5SV8 702-2KK	60
5SV8 702-2KP	60
5SV8 703-2KK	120
5SV8 704-2KK	210

Subject to change without notice
© Copyright Siemens

last modified: 4/11/2025

Subject to change without notice
© Copyright Siemens

Subject to change without notice
© Copyright Siemens