SIEMENS

Data sheet 6AG2552-1AA00-4AB0



Figure similar

SIPLUS S7-1500 TM timer DIDQ 16x 24 V rail based on 6ES7552-1AA00-0AB0 with conformal coating, -40…+70 °C, OT4 with ST1/2 (+85 °C for 10 minutes), time-controlled digital inputs and outputs max. 8 DI, 16 DQ of which max. 16 with time stamp, count, PWM, oversampling

General information	
Product type designation	TM Timer DIDQ 16x24V
based on	6ES7552-1AA00-0AB0
Product function	
● I&M data	Yes; I&M 0
● Isochronous mode	Yes
Engineering with	
● STEP 7 TIA Portal configurable/integrated from version	see entry ID: 109746275
Installation type/mounting	
Rail mounting	Yes; S7-1500 mounting rail
Supply voltage	
Load voltage 1L+	
● Rated value (DC)	24 V
● permissible range, lower limit (DC)	19.2 V
● permissible range, upper limit (DC)	28.8 V
● Reverse polarity protection	Yes; against destruction
Load voltage 2L+	
● Rated value (DC)	24 V
● permissible range, lower limit (DC)	19.2 V
● permissible range, upper limit (DC)	28.8 V
● Reverse polarity protection	Yes; against destruction
Input current	
from load voltage 1L+ (without load), max.	40 mA; without load
from load voltage 2L+ (without load), max.	30 mA; without load
Encoder supply	
Number of outputs	8; max. depending on parameterization
24 V encoder supply	
● 24 V	Yes; L+ (-0.8 V)
● Short-circuit protection	Yes
● Output current, max.	1.2 A; Total current of all encoders / channels, max. 0.5 A per output
Power	
Power consumption from the backplane bus	1.3 W
Power loss	
Power loss, typ.	5 W
Address area	
Address space per module	
● Inputs	44 byte
● Outputs	74 byte

Subject to change without notice
© Copyright Siemens

Digital inputs	
Number of digital inputs	8; max. depending on parameterization
Digital inputs, parameterizable	Yes
Input characteristic curve in accordance with IEC 61131, type 3	Yes
Digital input functions, parameterizable	
● Digital input with time stamp	Yes
— Number, max.	8
● Counter	Yes
— Number, max.	4
● Counter for incremental encoder	Yes
— Number, max.	4
● Digital input with oversampling	Yes
— Number, max.	8
● HW enable for digital input	Yes
— Number, max.	4
● HW enable for digital output	Yes
— Number, max.	4
Input voltage	
● Type of input voltage	DC
● Rated value (DC)	24 V
● for signal "0"	-5 ... +5 V
● for signal "1"	+11 to +30V
● permissible voltage at input, min.	-30 V; -5 V continuous, -30 V brief reverse polarity protection
● permissible voltage at input, max.	30 V
Input current	
● for signal "1", typ.	2.5 mA
Input delay (for rated value of input voltage)	
● Minimum pulse width for program reactions	3 µs; for parameterization "none"
for standard inputs	
— parameterizable	Yes; none / 0.05 / 0.1 / 0.4 / 0.8 ms
Cable length	
● shielded, max.	1 000 m; Depending on sensor, cable quality and rate of change
● unshielded, max.	600 m; Depending on sensor, cable quality and rate of change
Digital outputs	
Type of digital output	Transistor
Number of digital outputs	16; max. depending on parameterization
● in groups of	8
Current-sinking	Yes; With High Speed output
Current-sourcing	Yes
Digital outputs, parameterizable	Yes
Short-circuit protection	Yes; electronic/thermal
● Response threshold, typ.	1.7 A with Standard output, 0.5 A with High Speed output
Limitation of inductive shutdown voltage to	-0.8 V
Controlling a digital input	Yes
Digital output functions, parameterizable	
● Digital output with time stamp	Yes
— Number, max.	16
● PWM output	Yes
— Number, max.	16
● Digital output with oversampling	Yes
— Number, max.	16
Switching capacity of the outputs	
● with resistive load, max.	0.5 A; 0.1 A with High Speed output
● on lamp load, max.	5 W; 1 W with High Speed output
Load resistance range	
● lower limit	48 Ω; 240 ohm with High Speed output
● upper limit	12 kΩ
Output voltage	
● Type of output voltage	DC

Subject to change without notice
© Copyright Siemens

● for signal "0", max.	1 V; With High Speed output
● for signal "1", min.	23.2 V; L+ (-0.8 V)
Output current	
● for signal "1" rated value	0.5 A; 0.1 A with High Speed output, observe derating
● for signal "1" permissible range, max.	0.6 A; 0.12 A with High Speed output, observe derating
● for signal "1" minimum load current	2 mA
● for signal "0" residual current, max.	0.5 mA
Output delay with resistive load	
● "0" to "1", max.	1 µs; With High Speed output, 5 µs with Standard output
● "1" to "0", max.	1 µs; With High Speed output, 6 µs with Standard output
Switching frequency	
● with resistive load, max.	10 kHz
● on lamp load, max.	10 Hz
Total current of the outputs	
● Current per group, max.	4 A
● Current per module, max.	8 A; Observe derating
Cable length	
● shielded, max.	1 000 m; depending on load and cable quality
● unshielded, max.	600 m; depending on load and cable quality
Encoder	
Connectable encoders	
● Incremental encoder (asymmetrical)	Yes
● 24 V initiator	Yes
● 2-wire sensor	Yes
— permissible quiescent current (2-wire sensor), max.	1.5 mA
Encoder signals, incremental encoder (asymmetrical)	
● Input voltage	24 V
● Input frequency, max.	50 kHz
● Counting frequency, max.	200 kHz; with quadruple evaluation
● Cable length, shielded, max.	600 m; Depending on input frequency, encoder and cable quality; max. 200 m at 50 kHz
● Incremental encoder with A/B tracks, 90° phase offset	Yes
● pulse encoder	Yes
Interface types	
● Input characteristic curve in accordance with IEC 61131, type 3	Yes
Isochronous mode	
Bus cycle time (TDP), min.	250 µs
Jitter, max.	1 µs
Interrupts/diagnostics/status information	
Diagnostics function	Yes
Substitute values connectable	Yes
Alarms	
● Diagnostic alarm	Yes
Diagnoses	
● Monitoring the supply voltage	Yes
● Short-circuit	Yes
Diagnostics indication LED	
● RUN LED	Yes; green LED
● ERROR LED	Yes; red LED
● MAINT LED	Yes; Yellow LED
● Monitoring of the supply voltage (PWR-LED)	Yes; green LED
● Channel status display	Yes; green LED
● for channel diagnostics	Yes; red LED
Integrated Functions	
Counter	Yes
● Number of counters	4
● Counting frequency, max.	200 kHz; with quadruple evaluation
Counting functions	

Subject to change without notice
© Copyright Siemens

● Continuous counting	Yes
Position detection	
● Incremental acquisition	Yes
Potential separation	
Potential separation channels	
● between the channels and backplane bus	Yes
Isolation	
Isolation tested with	750 V DC (type test) and according to EN 50155 (routine test)
Standards, approvals, certificates	
Railway application	
● EN 50121-3-2	Yes; EMC for rail vehicles
● EN 50121-4	Yes; EMC for signal and telecommunications systems
● EN 50121-5	Yes; EMC for fixed installations and railway power supply equipment (shielded cables required)
● EN 50124-1	Yes; Railway applications - overvoltage category OV2; pollution degree PD2; rated surge voltage UNi = 0.5 kV; UNm = 24 V DC
● EN 50125-1	Yes; Rail vehicles - see ambient conditions
● EN 50125-2	Yes; Stationary electrical equipment - see ambient conditions
● EN 50125-3	Yes; Signal and telecommunications systems - see ambient conditions; vibrations and shocks: Application point outside of tracks (1 m to 3 m away from track)
● EN 50155	Yes; Rail vehicles - temperature class OT4, ST1/ST2, horizontal mounting position
● EN 61373	Yes; Rail vehicles - vibrations and shocks: Category 1 Class A/B
● Fire protection acc. to EN 45545-2	Yes; For proof of conformity, see Service & Support
Ambient conditions	
Ambient temperature during operation	
● horizontal installation, min.	-40 °C; = Tmin (incl. condensation/frost)
● horizontal installation, max.	70 °C; = Tmax; +85 °C for 10 min (OT4, ST1/ST2 acc. to EN 50155)
● vertical installation, min.	-40 °C; = Tmin
● vertical installation, max.	40 °C; = Tmax; Note derating
Altitude during operation relating to sea level	
● Installation altitude above sea level, max.	2 000 m
● Ambient air temperature-barometric pressure-altitude	Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m)
Relative humidity	
● With condensation, tested in accordance with IEC 60068-2-38, max.	100 %; RH incl. condensation / frost (no commissioning in bedewed state), horizontal installation
Resistance	
Coolants and lubricants	
— Resistant to commercially available coolants and lubricants	Yes; Incl. diesel and oil droplets in the air
Use in stationary industrial systems	
— to biologically active substances according to EN 60721-3-3	Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request
— to chemically active substances according to EN 60721-3-3	Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
— to mechanically active substances according to EN 60721-3-3	Yes; Class 3S4 incl. sand, dust, *
Use on land craft, rail vehicles and special-purpose vehicles	
— to biologically active substances according to EN 60721-3-5	Yes; Class 5B2 mold, fungus and dry rot spores (with the exception of fauna); Class 5B3 on request
— to chemically active substances according to EN 60721-3-5	Yes; Class 5C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
— to mechanically active substances according to EN 60721-3-5	Yes; Class 5S3 incl. sand, dust; *
Usage in industrial process technology	
— Against chemically active substances acc. to EN 60654-4	Yes; Class 3 (excluding trichlorethylene)
— Environmental conditions for process, measuring and control systems acc. to ANSI/ISA-71.04	Yes; Level GX group A/B (excluding trichlorethylene; harmful gas concentrations up to the limits of EN 60721-3-3 class 3C4 permissible); level LC3 (salt spray) and level LB3 (oil)
Remark	
— Note regarding classification of environmental conditions acc. to EN 60721, EN 60654-4 and	* The supplied plug covers must remain in place over the unused interfaces during operation!

Subject to change without notice
© Copyright Siemens

ANSI/ISA-71.04	
Conformal coating	
● Coatings for printed circuit board assemblies acc. to EN 61086	Yes; Class 2 for high reliability
● Protection against fouling acc. to EN 60664-3	Yes; Type 1 protection
● Electronic equipment on rolling stock acc. to EN 50155	Yes; Class PC2 protective coating acc. to EN 50155:2017
● Military testing according to MIL-I-46058C, Amendment 7	Yes; Discoloration of coating possible during service life
● Qualification and Performance of Electrical Insulating Compound for Printed Board Assemblies according to IPC-CC-830A	Yes; Conformal coating, Class A
Decentralized operation	
to SIMATIC S7-1500	Yes
Dimensions	
Width	35 mm
Height	147 mm
Depth	129 mm
Weights	
Weight, approx.	320 g
Other	
Note:	for use in railway applications, also observe the product information "SIPLUS extreme RAIL" A5E37661960A, Online Support article 109736776

Classifications

	Version	Classification
eClass	16	27-24-22-05
eClass	14	27-24-22-05
eClass	12	27-24-22-05
eClass	9.1	27-24-22-05
eClass	9	27-24-22-05
eClass	8	27-24-22-05
eClass	7.1	27-24-22-05
eClass	6	27-24-22-05
ETIM	10	EC001422
ETIM	9	EC001422
ETIM	8	EC001422
ETIM	7	EC001422

Approvals / Certificates

General Product Approval

China RoHS

General Product Approval	EMV	Railway
China RoHS		Confirmation

last modified: 7/3/2026

Subject to change without notice
© Copyright Siemens