SIEMENS

Data sheet for SIMOTICS S-1FK7

Article No. : **1FK7015-5AK71-1JH3**



Figure similar

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data	
Rated speed (100 K)	6,000 rpm
Number of poles	8
Rated torque (100 K)	0.2 Nm
Rated current	0.8 A
Static torque (60 K)	0.29 Nm
Static torque (100 K)	0.35 Nm
Stall current (60 K)	1.20 A
Stall current (100 K)	1.50 A
Moment of inertia	0.102 kgcm²
Efficiency	68.0 %

Physical constants	
Torque constant	0.24 Nm/A
Voltage constant at 20° C	16.0 V/1000*min⁻¹
Winding resistance at 20° C	4.30 Ω
Rotating field inductance	8.4 mH
Electrical time constant	2.00 ms
Mechanical time constant	1.90 ms
Thermal time constant	16 min
Shaft torsional stiffness	1,300 Nm/rad
Net weight of the motor	1.2 kg

Mechanical data	
Motor type	Permanent-magnet synchronous motor
Motor type	Compact
Shaft height	20
Cooling	Natural cooling
Radial runout tolerance	0.000 mm
Concentricity tolerance	0.00 mm
Axial runout tolerance	0.00 mm
Vibration severity grade	Grade A
Connector size	M17
Degree of protection	IP54
Design acc. to Code I	IM B5 (IM V1, IM V3)
Temperature monitoring	KTY84 temperature sensor in the stator winding
Electrical connectors	Connectors for signals and power rotatable
Color of the housing	Standard (Anthracite RAL 7016)
Holding brake	with holding brake
Shaft end	Plain shaft
Encoder system	Encoder AM16S/R: absolute encoder 16 S/R, 4096 revolutions multi-turn, with EnDat interface

Optimum operating point	
Optimum speed	5,000 rpm
Optimum power	0.1 kW

Limiting data	
Max. permissible speed (mech.)	8,000 rpm
Max. permissible speed (inverter)	8,000 rpm
Maximum torque	1.0 Nm
Maximum current	4.2 A

Holding brake	
Holding brake version	Permanent-magnet brake
Holding torque	0.4 Nm
Power supply voltage	DC 24 V ± 10 %
Coil current	0.3 A
Opening time	30 ms
Closing time	20 ms
Highest braking work	2 J

Recommended Motor Module	
Rated inverter current	3 A
Maximum inverter current	6 A
Maximum torque	1.00 Nm

Subject to change. Calculated values may differ from nameplate ratings. © Copyright Siemens