SIEMENS

Data sheet 4EU2722-6BA00-0AA0



Figure similar

line commutating reactor for rectifier; phases: 3; Un1(V): 400; Ithmax 1(A) / F1(Hz): 250 /50; I LN (A): 225; UK(%): 4; LN(MH): 0.0849; temperature rise/insulation class: 40 /H; IP00; connection: flat-type; EN 61558-2-20 >reactor<

General technical data		
product designation		Kommut.-Drossel f. Stromrichter
phase number		3
type of voltage		AC
operating voltage rated value	V	400
operating frequency rated value	Hz	50
•		
— operational current at AC rated value	A	225
— current at AC maximum	A	250
• current at DC rated value	A	306.3
peak current	A	313
inductivity rated value	H	8.4E-5
relative inductive drop in voltage for rated value of the current, voltage and frequency	%	4
power loss [W] of the coil	W	174
power loss [W] of the iron core	W	75
Mechanical data		
type of electrical connection for main current circuit		flat connector
width	m	0.27
height	m	0.248
depth	m	0.187
Ambient conditions		
thermal class according to IEC 60085		H
ambient temperature rated value	°C	40
protection class IP		IP00

Certificates/ approvals

General Product Approval	other	Environment
EAC	Confirmation	产品合格 QC PASS
		Environmental Confirmations

Further information

Information on the packaging
https://support.industry.siemens.com/cs/ww/en/view/109813875
Information for data generation and storage

Subject to change without notice
© Copyright Siemens

https://support.industry.siemens.com/cs/ww/en/view/109995012

Information- and Downloadcenter (Catalogs, Brochures,…)
https://www.siemens.com/ic10

Industry Mall (Online ordering system)
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=4EU2722-6BA00-0AA0

Cax online generator
https://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=4EU2722-6BA00-0AA0

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
https://support.industry.siemens.com/cs/ww/en/ps/4EU2722-6BA00-0AA0

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)
https://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=4EU2722-6BA00-0AA0&lang=en

---

last modified: 4/8/2025

Subject to change without notice
© Copyright Siemens