SIEMENS

Data sheet 6AT8002-4AC03

SIPLUS CMS2000 cable MIL-300 Connecting cable for connection of VIB sensors with MIL connectors; Length=3.00 m



General information	
Product type designation	Cable MIL-300
Product description	For connection of the VIB-SENSOR S01 vibration sensor to the SIPLUS CMS2000 Basic Unit VIB or the SIPLUS CMS2000 VIB-MUX expansion module
Ambient conditions	
Ambient temperature during operation	
● min.	-25 °C
● max.	122 °C
Cables	
Type of insulation	black polyurethane
Design of shield	Braided shielding with stranded drain wire
Cable length	3 m
Connection method	
Type of connection	MIL-C5015 / open cable end

Classifications

	Version	Classification
eClass	16	27-20-90-90
eClass	14	27-20-90-90
eClass	12	27-20-90-90
eClass	9.1	27-20-90-90
eClass	9	27-20-90-90
eClass	8	27-20-90-90
eClass	7.1	27-20-90-90
eClass	6	27-20-90-90
ETIM	10	EC001195
ETIM	9	EC001195
ETIM	8	EC001195
ETIM	7	EC001195

Approvals / Certificates

General Product Approval	EMV

Subject to change without notice
© Copyright Siemens

last modified:	5/9/2025

Subject to change without notice
© Copyright Siemens