SIEMENS

Data sheet 6GK5826-2AB00-2AB2

product type designation	**M826-2 SHDSL**
	SCALANCE M826-2 SHDSL router; for the IP communication via 2-wire and 4-wire cables from Ethernet-based Programmable controllers; SHDSL topology: Point-to-point, bonding, line bridge mode; Routing mode with VPN, Firewall, NAT; 4-port switch; 1x digital input, 1x digital output



product brand name	SCALANCE
Technical Product Detail Page	https://i.siemens.com/1P6GK5826-2AB00-2AB2
transfer rate	
transfer rate / for Industrial Ethernet	10, 100 Mbit/s
transfer rate	
● for SHSDL transmission / maximum	15.3 Mbit/s
interfaces	
number of electrical connections	
● for internal network	4
● for external network	2
number of electrical connections	
● for power supply	2
type of electrical connection	
● for internal network	RJ45 port (10/100 Mbit/s, TP, autocrossover)
● for external network	Terminal strip
● for power supply	Terminal strip
WAN connection	
type of WAN connection / is supported / SHSDL	Yes
supply voltage, current consumption, power loss	
supply voltage / rated value	10.8 ... 28.8
consumed current	
● at DC / at 24 V / typical	0.29 A
supply voltage / 1 / rated value	24 V
● type of voltage / 1 / of the supply voltage	DC
ambient conditions	
ambient temperature	
● during operation	-40 ... +70 °C
● during storage	-40 ... +80 °C
relative humidity / at 25 °C / during operation / maximum	95 %
protection class IP	IP20
design, dimensions and weights	
design	compact
depth	127 mm
height	147 mm
width	35 mm
net weight	393 g
fastening method	
● 35 mm DIN-rail mounting	Yes

Subject to change without notice
© Copyright Siemens

● S7-300 rail mounting	Yes
● S7-1500 rail mounting	Yes
● wall mounting	Yes
product features, product functions, product components / general	
product function	
● DynDNS client	Yes
● no-ip.com client	Yes
product functions / management, configuration, engineering	
product function	
● CLI	Yes
● web-based management	Yes
● MIB support	Yes
● TRAPs via email	Yes
protocol / is supported	
● Telnet	Yes
● HTTP	Yes
● HTTPS	Yes
type of configuration	Web-based management
product function / is supported / identification link	Yes; acc. to IEC 61406-1:2022
product functions / diagnostics	
protocol / is supported	
● SNMP v1	Yes
● SNMP v2	Yes
● SNMP v2c	Yes
● SNMP v3	Yes
product function	
● statistics Packet Size	No
● statistics packet type	No
● error statistics	No
● SysLog	Yes
● packet filter log	Yes
product functions / DHCP	
product function	
● DHCP client	Yes
● DHCP server - internal network	Yes
product functions / routing	
router function	
● NAT (IP masquerading)	Yes
● port forwarding	Yes
● NAT traversal	Yes
● 1:1 NAT	Yes
● DNS cache	Yes
product functions / security	
suitability for operation / Virtual Private Network	Yes
firewall version	Statefull Inspection
product function	
● password protection	Yes
● packet filter	Yes
● broadcast/multicast/unicast limiter	No
product function	
● broadcast blocking	No
● with VPN connection	IPsec, OpenVPN (as Client)
number of possible connections / with VPN connection	20
type of authentication / with Virtual Private Network / PSK	Yes
protocol / is supported	
● IPsec tunnel and transport mode	Yes
key length	
● 1 / with IPsec AES / with Virtual Private Network	128 bit
● 2 / with IPsec AES / with Virtual Private Network	192 bit

Subject to change without notice
© Copyright Siemens

● 3 / with IPsec AES / with Virtual Private Network	256 bit
● with IPsec 3DES / with Virtual Private Network	168 bit
type of internet key exchange / with Virtual Private Network	
● main mode	Yes
● quick mode	Yes
type of packet authentication / with Virtual Private Network	MD5, SHA-1, SHA-256, SHA-384, SHA-512
IETF profile / with Virtual Private Network / X.509v3 certificate	Yes
product functions / time	
protocol / is supported	
● NTP	Yes
● SNTP	Yes
standards, specifications, approvals	
standard	
● for FM	FM16US0205X, FM 3611: Class I, Division 2, Groups A,B,C,D, T4 / Class 1, Zone 2, Group IIC, T4
● for hazardous zone	EN 60079-15, EN 60079-0, II 3 G Ex nA IIC T4 Gc, KEMA 07ATEX0145 X
● for safety / from CSA and UL	UL 60950-1 E115352 Vol. X2
● for hazardous zone / from CSA and UL	ANSI/ISA 12.12.01-2013, CAN/CSA C22.2 No.213-M1987, Cl. 1, div. 2, GP. A, B, C, D, T4 / Cl. 1, Zone 2, GP IIC E240480
certificate of suitability	
● CE marking	Yes
● CCC approval	Yes; GB3836.1, GB3836.8, Ex nA IIC T4 Gc
● railway application in accordance with EN 50121-3-2	Yes
● railway application in accordance with EN 50121-4	Yes
● railway application in accordance with EN 50155	Yes; no coated printed circuit boards
● railway application in accordance with EN 61373	Yes; cat. 1, cl.A and cl. B
Marine classification association	
● American Bureau of Shipping Europe Ltd. (ABS)	Yes
● French marine classification society (BV)	Yes
● DNV GL	Yes
● Korean Register of Shipping (KRS)	Yes
● Lloyds Register of Shipping (LRS)	Yes
● Nippon Kaiji Kyokai (NK)	Yes
● Polski Rejestr Statkow (PRS)	Yes
● Royal Institution of Naval Architects (RINA)	Yes
standards, specifications, approvals / Environmental Product Declaration	
Environmental Product Declaration	Yes
global warming potential [CO2 eq]	
● total	239.6256 kg
● during manufacturing	20.1 kg
● during operation	219 kg
● after end of life	0.456 kg
further information / internet links	
internet link	
● to website: Selection guide for cables and connectors	https://support.industry.siemens.com/cs/ww/en/view/109766358
● to web page: selection aid TIA Selection Tool	https://www.siemens.com/tstcloud
● to website: Industrial communication	https://www.siemens.com/simatic-net
● to web page: SiePortal	https://sieportal.siemens.com/
● to website: Image database	https://www.automation.siemens.com/bilddb
● to website: CAx-Download-Manager	https://www.siemens.com/cax
● to website: Industry Online Support	https://support.industry.siemens.com
security information	
security information	Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement - and continuously maintain - a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or

© Copyright Siemens

network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under https://www.siemens.com/cert. (V4.7)

Approvals / Certificates

General Product Approval

Declaration of Conformity | China RoHS | Manufacturer Declaration

General Product Approval | For use in hazardous locations

China RoHS | FM

For use in hazardous locations | Maritime application

CCC-Ex | NK / Nippon Kaiji Kyokai

Maritime application | Railway | Environment | Industrial Communication

Confirmation | PROFINET

last modified: 3/10/2026

Subject to change without notice
© Copyright Siemens