SIEMENS

Data sheet 3RW4900-0KC00



Communication module PROFIBUS for SIRIUS soft starter 3RW44 Required firmware version 3RW44 >= *E06*. implemented for starters 3RW44 from delivery date May 2006

product brand name	SIRIUS
product category	Communication modules
product designation	Communication module
design of the product	for 3RW44 soft starter integration in the PROFIBUS network with DPV1 slave functionality. From module firmware version E04 and higher (and/or date of manufacture May 1, 2009 or later), DPV1 operation of the soft starter on a Y-link is also possible (only DPV0 operation possible with < E04)
product type designation	3RW49
General technical data	
Substance Prohibitance (day/month/year)	05/01/2012
SVHC substance name	Lead CAS-No. 7439-92-1 Lead monoxide (lead oxide) CAS-No. 1317-36-8 2-methyl-1-(4-methylthiophenyl)-2-morpholinopropan-1-one CAS-No. 71868-10-5 Melamine CAS-No. 108-78-1
Net Weight	0.149 kg
Installation/ mounting/ dimensions	
height	117.3 mm
width	36.6 mm
depth	88.5 mm
Electrical Safety	
protection class IP on the front according to IEC 60529	IP20
touch protection on the front according to IEC 60529	finger-safe, for vertical contact from the front
Approvals Certificates	

Environment	General Product Approval				EMV
Environmental Confirmations	cULus	EAC	CE EG-Konf.	UKCA	KC

EMV	Test Certificates	Maritime application			
RCM	Special Test Certificate	ABS	DNV	LRS	PRS

other


Subject to change without notice
© Copyright Siemens


Confirmation




Further information

Information on the packaging
https://support.industry.siemens.com/cs/ww/en/view/109813875
Information for data generation and storage
https://support.industry.siemens.com/cs/ww/en/view/109995012
Information- and Downloadcenter (Catalogs, Brochures,…)
https://www.siemens.com/ic10
Industry Mall (Online ordering system)
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RW4900-0KC00
Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
https://support.industry.siemens.com/cs/ww/en/ps/3RW4900-0KC00
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)
https://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RW4900-0KC00&lang=en
Cax online generator
https://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RW4900-0KC00
Kennlinien
https://curves.simaris.siemens.com/curves/3RW4900-0KC00
Characteristic: Tripping characteristics, I²t, Let-through current
https://support.industry.siemens.com/cs/ww/en/ps/3RW4900-0KC00/char
Characteristic: Installation altitude
https://www.automation.siemens.com/bilddb/index.aspx?gridview=view2&objkey=G_NSB0_XX_01704&showdetail=true&view=Search
Simulation Tool for Soft Starters (STS)
https://support.industry.siemens.com/cs/ww/en/view/101494917





Subject to change without notice
© Copyright Siemens



last modified: 5/5/2026

Subject to change without notice
© Copyright Siemens

Subject to change without notice
© Copyright Siemens