SIEMENS

Data sheet for SINUMERIK BEDIENTAFELFRONT TP 015A



Figure similar

Article No. : 6FC5203-0AF08-0AB2

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Screen	
Screen diagonal	15.0 in TFT color XGA
Screen resolution	1,024 x 768

Rated data	
Input voltage	DC 5 V
	Via PCU or TCU
Power consumption	
Maximum	25.0 W
Standard	15.0 W

Mechanical data	
Net weight	8.4 kg (18.52 lb)
Width	483 mm (19.02 in)
Height	355.0 mm (13.98 in)
Depth	53 mm (2.09 in)
	Without USB protective cover on the front
Installation depth	42.0 mm (1.65 in)
with PCU 50	127.0 mm (5.00 in)
	Clearance + 10 mm (0.39 in)
Mounting surface	
Cutout width	450.0 mm (17.72 in)
Cutout height	335.0 mm (13.19 in)
Degree of protection	
Front side	IP65
Rear side	IP00

Ambient conditions	
Climate class according to EN60721-3-3	Condensation and icing excluded. Low air temperature 0 °C (32 °F).
Ambient temperature	
Operation on the front	0 ... 45 °C (32 ... 113 °F)
Operation at the rear	0 ... 55 °C (32 ... 131 °F)
Storage	-20 ... 55 °C (-4 ... 131 °F)
Transport	-20 ... 55 °C (-4 ... 131 °F)
Relative humidity	
Operation	5 ... 95 %
Storage	5 ... 95 %
Transport	5 ... 95 %

Approvals	
Certificate of suitability	CE / cULus