SIEMENS

Data sheet for SIMOTICS S-1FT7




Figure similar

Article No. : 1FT7132-5AF71-1BG5

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data	
Rated speed	3,000 rpm
Number of poles	8
Rated torque (100 K)	27.0 Nm
Rated current	14.00 A
Static torque (60 K)	75.0 Nm
Static torque (100 K)	90.0 Nm
Stall current (60 K)	36.00 A
Stall current (100 K)	43.50 A
Rotor moment of inertia	459.00 kgcm²
Efficiency	94.0 %

Physical constants	
Torque constant	2.08 Nm/A
Voltage constant at 20° C	137.0 V/1000*min^{-1}
Winding resistance at 20° C	0.06 Ω
Rotary field inductance	2.0 mH
Electrical time constant	32.00 ms
Mechanical time constant	2.00 ms
Thermal time constant	75 min
Shaft torsional stiffness	347,000 Nm/rad
Net weight of the motor	77.0 kg

Mechanical data	
Motor type	Permanent-magnet synchronous motor
Motor type	Compact
Shaft height	132
Cooling	Natural cooling
Radial runout tolerance	0.050 mm
Concentricity tolerance	0.125 mm
Axial runout tolerance	0.125 mm
Vibration severity grade	Grade R
Degree of protection	IP67
Design acc. to Code I	IM B5 (compatible with 1FT6)
Temperature monitoring	Pt1000 temperature sensor
Color of the housing	Standard (pearl dark gray similar to RAL 9023)
Shaft end type	Plain shaft
Sensor design	Encoder AS24DQI: Absolut encoder Singleturn 24 bit - with signal connection RJ45
Safety Integrated - Suitable encoder	Yes
Electrical connection	Transverse facing to right site
Connector size	3

Optimum operating point	
Optimum speed	2,150 rpm
Optimum power	12.0 kW

Limiting data	
Max. permissible speed (mech.)	3,600 rpm
Max. permissible speed (inverter)	3,600 rpm
Maximum torque	290.0 Nm
Maximum current	172.00 A

Recommended Motor Module	
Rated inverter current	45.00 A
Maximum inverter current	85.00 A
Maximum torque	168.0 Nm

Subject to change. Calculated values may differ from nameplate ratings. © Copyright Siemens