SIEMENS

Data sheet 3UF7910-0AA00-0

Addressing plug, for assigning the PROFIBUS address to SIMOCODE pro without PC/PG



General technical data	
product brand name	SIMOCODE
product designation	addressing plug
design of the product	For assigning the PROFIBUS or Modbus RTU address without using a PC/PG
ambient temperature	
● during storage	-40 ... +80 °C
● during operation	-25 ... +60 °C
● during transport	-40 ... +80 °C

Certificates/ approvals

General Product Approval

CCC, cULus, UL, EAC, CE EG-Konf., UKCA

EMV	Test Certificates	Maritime application
KC, RCM	Type Test Certificates/Test Report	ABS, DNV, LRS

other	Environment	Industrial Communication
Confirmation, 产品合格 QC PASS	Environmental Confirmations	Profibus

Further information

Information on the packaging
https://support.industry.siemens.com/cs/ww/en/view/109813875
Information for data generation and storage
https://support.industry.siemens.com/cs/ww/en/view/109995012
Information- and Downloadcenter (Catalogs, Brochures,…)
https://www.siemens.com/ic10
Industry Mall (Online ordering system)
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3UF7910-0AA00-0
Cax online generator
https://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3UF7910-0AA00-0

Subject to change without notice
© Copyright Siemens

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
https://support.industry.siemens.com/cs/ww/en/ps/3UF7910-0AA00-0
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)
https://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3UF7910-0AA00-0&lang=en



Subject to change without notice
© Copyright Siemens



Subject to change without notice
© Copyright Siemens