SIEMENS

Data sheet 3VL1705-1DD36-0AA0

circuit breaker VL160X N standard breaking capacity Icu=55kA, 415V AC 3-pole, line protection Trip Unit TM, LI In=50A, rated current Ir=40...50A, overload prot. II=600A, short-circuit prot. with screw terminals without auxiliary release without auxiliary/alarm switch, spare part product only for replacement purposes

Weight	2.933 kg
Net Weight	2.933 kg

Approvals / Certificates

Environment		General Product Approval			Test Certificates
Environmental Confirmations	Environmental Confirmations	EAC	Confirmation	UKCA	Special Test Certificate

other

Miscellaneous	Confirmation	产品合格 QC PASS	Miscellaneous

Further information

Information on the packaging
https://support.industry.siemens.com/cs/ww/en/view/109813875
Information for data generation and storage
https://support.industry.siemens.com/cs/ww/en/view/109995012
Information- and Downloadcenter (catalogues, leaflets,...)
https://www.siemens.com/energy-automation
Industry Mall (Online ordering system)
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VL1705-1DD36-0AA0
Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
https://support.industry.siemens.com/cs/ww/en/ps/3VL1705-1DD36-0AA0
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)
https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VL1705-1DD36-0AA0
CAx-Online-Generator
https://www.siemens.com/cax
Kennlinien
https://curves.simaris.siemens.com/curves/3VL1705-1DD36-0AA0

last modified: 11/24/2025

Subject to change without notice
© Copyright Siemens

Subject to change without notice
© Copyright Siemens