SIEMENS

Data sheet 6AG4104-3KT34-4GA0

No longer available SIMATIC IPC547E (rack PC, 19", 4HU); Interfaces: 2x USB 3.0 front, 1x DVI-I, 6x USB 2.0 on the rear side, 2x PS/2, audio; 7 slots: 2x PCIe X16, 1x PCIE X8, 4x PCI; temperature and fan monitoring; Watchdog; card retainer Core I7-4770S (4C/8T, 3.1(3.9) GHz, 8 MB cache, IAMT), 2x Gbit Ethernet, 2x display ports V1.2, 2x USB 3.0 on the rear side, 1x USB 2.0 internal, 1x COM1 RAID5, 2 TB (3x 1 TB HDD, striping with parity) in removable frame; hot-swap, on the front and 1x 1 TB HDD as hot spare in removable frame; front-side 8 GB DDR3 SD-RAM (2x 4 GB), Dual Channel Enclosure painted, DVD +/-RW (SLIM) Serial (COM2)+parallel (LPT) and PCIE X16 graphics card (DH: 2x VGA O. 2x DVI-D); 512 MB Windows Server 2012 R2 Standard edition incl. 5 clients MUI (de, en, fr, es, it), 64 bit SIMATIC IPC DIAGMONITOR V4.5 enclosed 100/240V industrial power supply unit; Power supply cable Europe

Approvals / Certificates

General Product Approval					Dangerous goods
Miscellaneous	Manufacturer Declaration		BIS CRS	China RoHS	Test Summary Report UN 38.3

Dangerous goods

Dangerous goods information	Dangerous goods information	Test Summary Report UN 38.3

last modified: 11/24/2025

Subject to change without notice
© Copyright Siemens