SIEMENS

Data sheet 3RX9306-1AA00

AS-Interface combi-power supply IP20, AS-Interface 30 V DC, 4 A with data decoupling 24 V DC, 5 A (primary clocking) Input voltage 115 V/230 V AC reconnectable

Safety related data		
protection class IP		IP20
Ambient conditions		
ambient temperature		
● during operation	°C	-45 ... +55
● during storage	°C	-45 ... +60
fastening method		fixing on standard mounting rail DIN EN 50 022-35 x 7.5 mm snap-on
width	mm	150
height	mm	135
depth	mm	107

Certificates/ approvals

Environment	General Product Approval	other
Environmental Confirmations	EAC	Confirmation 产品合格 QC PASS

Further information

Information on the packaging
https://support.industry.siemens.com/cs/ww/en/view/109813875
Information for data generation and storage
https://support.industry.siemens.com/cs/ww/en/view/109995012
Information- and Downloadcenter (Catalogs, Brochures,…)
https://www.siemens.com/ic10
Industry Mall (Online ordering system)
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RX9306-1AA00
Cax online generator
https://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RX9306-1AA00
Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
https://support.industry.siemens.com/cs/ww/en/ps/3RX9306-1AA00
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)
https://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RX9306-1AA00&lang=en

last modified: 4/4/2026

Subject to change without notice
© Copyright Siemens