SIEMENS

## Data sheet 3SU1001-6AA70-0AA0



Indicator lights, 22 mm, round, plastic, clear, lens, smooth

| | |
|---|---|
| **product brand name** | SIRIUS ACT |
| **product designation** | Indicator lights |
| **design of the product** | Actuating/signaling element |
| **product type designation** | 3SU1 |
| **product line** | Plastic, black, 22 mm |
| **Actuator** | |
| **product extension optional** | |
| ● light source | Yes |
| ● contact module | No |
| **color** | |
| ● of the actuating element | clear |
| ● of the cover cap | transparent |
| **material of the actuating element** | plastic |
| **shape of the actuating element** | round |
| **outer diameter of the actuating element** | 29.45 mm |
| **Front ring** | |
| **product component front ring** | No |
| **material of the front ring** | plastic |
| **color of the front ring** | black |
| **General technical data** | |
| **protection class IP** | IP66, IP67, IP69(IP69K) |
| **degree of protection NEMA rating** | 1, 2, 3, 3R, 4, 4X, 12, 13 |
| **shock resistance** | |
| ● **according to IEC 60068-2-27** | sinusoidal half-wave 15 g / 11 ms |
| ● for railway applications according to EN 61373 | Category 1, Class B |
| **vibration resistance** | |
| ● **according to IEC 60068-2-6** | 10 ... 500 Hz: 5 g |
| ● for railway applications according to EN 61373 | Category 1, Class B |
| **reference code according to IEC 81346-2** | P |
| **Substance Prohibitance (day/month/year)** | 10/01/2014 |
| **Net Weight** | 0.011 kg |
| **Connections/ Terminals** | |
| **tightening torque of the screws in the bracket** | 1 ... 1.2 N·m |
| **Ambient conditions** | |
| **ambient temperature** | |
| ● during operation | -25 ... +70 °C |


Subject to change without notice
© Copyright Siemens

| | |
|---|---|
| ● during storage | -40 ... +80 °C |
| environmental category during operation according to IEC 60721 | 3M6, 3S2, 3B2, 3C3, 3K6 (with relative air humidity of 10 ... 95%) |

| Installation/ mounting/ dimensions | |
|---|---|
| **height** | 29.5 mm |
| **width** | 29.5 mm |
| **shape of the installation opening** | round |
| **mounting diameter** | 22.3 mm |
| **positive tolerance of installation diameter** | 0.4 mm |
| **mounting height** | 11.8 mm |
| **installation width** | 29.5 mm |
| **installation depth** | 24.4 mm |

| Environmental footprint | |
|---|---|
| Environmental Product Declaration(EPD) | Yes |
| global warming potential [CO2 eq] total | 0.787 kg |
| global warming potential [CO2 eq] during manufacturing | 0.566 kg |
| global warming potential [CO2 eq] during operation | 0.235 kg |
| global warming potential [CO2 eq] after end of life | -0.015 kg |
| Siemens eco profile (SEP) | Siemens EcoTech |

| Approvals Certificates | |
|---|---|
| Environmental Product Declaration | |
| ● global warming potential [CO2 eq] / during manufacturing | 0.566 kg |
| ● global warming potential [CO2 eq] / during operation | 0.235 kg |
| ● global warming potential [CO2 eq] / after end of life | -0.0145 kg |
| ● global warming potential [CO2 eq] / total | 0.787 kg |

**Environment**

Environmental Confirmations

**General Product Approval**

**General Product Approval**

**Test Certificates**

Type Test Certificates/Test Report

Special Test Certificate

**Maritime application**

**Maritime application**


**other**

Confirmation

## Further information

**Information on the packaging**
https://support.industry.siemens.com/cs/ww/en/view/109813875
**Information for data generation and storage**
https://support.industry.siemens.com/cs/ww/en/view/109995012
**Information- and Downloadcenter (Catalogs, Brochures,…)**
https://www.siemens.com/ic10
**Industry Mall (Online ordering system)**
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SU1001-6AA70-0AA0
**Cax online generator**
https://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SU1001-6AA70-0AA0
**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**
https://support.industry.siemens.com/cs/ww/en/ps/3SU1001-6AA70-0AA0
**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)**
https://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SU1001-6AA70-0AA0&lang=en


© Copyright Siemens




**last modified:** 4/4/2026


Subject to change without notice
© Copyright Siemens