SIEMENS

Data sheet 6FC5370-8AA30-0BA0



spare part SINUMERIK 828D numerical control CNC hardware PPU 290.3 vertical

general information	
product brand name	SINUMERIK
product designation	CNC control
product type designation	828D
product short term	PPU 290.3
performance data	
consumed active power / maximum	60 W
relative positive tolerance / at DC / at 24 V	20 %
relative negative tolerance / at DC / at 24 V	15 %
buffering time / in the event of power failure	3 ms; 20 ms mit SITOP smart power supply
display	
design of the display	TFT color
screen diagonal	15.6 in
horizontal image resolution / of the display	1 366 pixel
vertical image resolution / of the display	768 pixel
degree of protection, protection class	
protection class IP / on the front	IP65
protection class IP / rear side	IP20 / UL open type
standards, approvals, certificates	
reference code / according to IEC 81346-2	K
ambient conditions	
environmental category / according to IEC 60721-3-3	Condensation and icing excluded. Low air temperature 0 °C (32 °F).
Substance Prohibitance (day/month/year)	08/01/2016
SVHC substance name	Lead CAS-No. 7439-92-1 Lead monoxide (lead oxide) CAS-No. 1317-36-8 4,4'-isopropylidenediphenol (Bisphenol A, BPA) CAS-No. 80-05-7 1,6,7,8,9,14,15,16,17,17,18,18-Dodecachloropentacyclo[12.2.1.16,9.02,13.05,10]octadeca-7,15-diene (“Dechlorane Plus”™) covering any of its individual anti- and syn-isomers or any combination thereof CAS-No. -
ambient temperature	
● on the front / during operation	0 ... 45 °C, 32 ... 113 °F
● rear side / during operation	0 ... 55 °C, 32 ... 131 °F
● during transport	-20 ... +60 °C, -4 ... +140 °F
● during storage	-25 ... +55 °C, -13 ... +131 °F
relative humidity	
● at 25 °C / during operation	5 ... 90 %
● at 25 °C / during transport	5 ... 95 %
● at 25 °C / during storage	10 ... 100 %
type of design, assembly	

Subject to change without notice
© Copyright Siemens

mounting position / of operating panel	Vertical

design, dimensions, weights

width	416 mm, 16.38 in
height	470 mm, 18.5 in
depth	105 mm, 4.13 in
net weight	8.9 kg, 19.62 lb

Classifications

	Version	Classification
eClass	16	27-24-21-02
eClass	14	27-24-21-02
eClass	12	27-24-21-02
eClass	9.1	27-24-21-02
eClass	9	27-24-21-02
eClass	8	27-24-21-02
eClass	7.1	27-24-21-02
eClass	6	27-24-21-02
ETIM	10	EC001422
ETIM	9	EC001422
ETIM	8	EC001422
ETIM	7	EC001422

Approvals / Certificates

General Product Approval					EMV
CE EG-Konf.	UKCA	Declaration of Conformity	UKCA	CE EG-Konf.	RCM

EMV	Functional Saftey	
KC	Manufacturer Declaration	Manufacturer Declaration

Subject to change without notice
© Copyright Siemens