SIEMENS

## Data sheet for SIMOTICS S-1FT7



Figure similar

**Article No. :** 1FT7034-5AK70-1BA0

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

| Engineering data | |
|---|---|
| Rated speed | 6,000 rpm |
| Number of poles | 6 |
| Rated torque (100 K) | 1.4 Nm |
| Rated current | 2.10 A |
| Static torque (60 K) | 1.6 Nm |
| Static torque (100 K) | 2.0 Nm |
| Stall current (60 K) | 2.10 A |
| Stall current (100 K) | 2.70 A |
| Rotor moment of inertia | 0.85 kgcm² |
| Efficiency | 90.0 % |

| Physical constants | |
|---|---|
| Torque constant | 0.76 Nm/A |
| Voltage constant at 20° C | 48.5 V/1000*min$^{-1}$ |
| Winding resistance at 20° C | 2.40 Ω |
| Rotary field inductance | 9.7 mH |
| Electrical time constant | 4.00 ms |
| Mechanical time constant | 1.10 ms |
| Thermal time constant | 25 min |
| Shaft torsional stiffness | 5,100 Nm/rad |
| Net weight of the motor | 3.8 kg |

| Mechanical data | |
|---|---|
| Motor type | Permanent-magnet synchronous motor |
| Motor type | Compact |
| Shaft height | 36 |
| Cooling | Natural cooling |
| Radial runout tolerance | 0.035 mm |
| Concentricity tolerance | 0.080 mm |
| Axial runout tolerance | 0.080 mm |
| Vibration severity grade | Grade A |
| Degree of protection | IP64 |
| Design acc. to Code I | IM B5 (new flange design) |
| Temperature monitoring | Pt1000 temperature sensor |
| Color of the housing | Standard (pearl dark gray similar to RAL 9023) |
| Shaft end type | Fitted key and keyway |
| Sensor design | Encoder AS24DQI: Absolut encoder Singleturn 24 bit - with signal connection RJ45 |
| Safety Integrated - Suitable encoder | Yes |
| Electrical connection | Connector turnable |
| Connector size | 1 |

| Optimum operating point | |
|---|---|
| Optimum speed | 6,000 rpm |
| Optimum power | 0.9 kW |

| Limiting data | |
|---|---|
| Max. permissible speed (mech.) | 10,000 rpm |
| Max. permissible speed (inverter) | 10,000 rpm |
| Maximum torque | 8.0 Nm |
| Maximum current | 12.00 A |

| Recommended Motor Module | |
|---|---|
| Rated inverter current | 3.00 A |
| Maximum inverter current | 9.00 A |
| Maximum torque | 6.3 Nm |

Subject to change. Calculated values may differ from nameplate ratings. © Copyright Siemens