SIEMENS

Data sheet 5ST3768

Infeed terminal 25 mm2 short for pin busbars



Model	
product brand name	SENTRON
product designation	Feeder terminal
Supply voltage	
operating voltage at AC rated value	690 V
Connections	
connectable conductor cross-section for copper cable	
● finely stranded with wire end sleeve minimum	4 mm²
● finely stranded with wire end sleeve maximum	16 mm²
● solid minimum	6 mm²
● solid maximum	25 mm²
● stranded minimum	6 mm²
● stranded maximum	25 mm²
tightening torque	
● minimum	1 N·m
● maximum	2 N·m
Mechanical Design	
height	17.7 mm
width	17 mm
depth	16.8 mm
length	38.2 mm
Net Weight	12 g

Approvals Certificates

Environment		General Product Approval		other
Environmental Confirmations	Environmental Confirmations	Miscellaneous	Confirmation	Confirmation

other

产品合格
QC PASS

Further information

Information on the packaging

Subject to change without notice
© Copyright Siemens

https://support.industry.siemens.com/cs/ww/en/view/109813875

Information for data generation and storage
https://support.industry.siemens.com/cs/ww/en/view/109995012

Information- and Downloadcenter (Catalogs, Brochures,…)
https://www.siemens.com/lowvoltage/catalogs

Industry Mall (Online ordering system)
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5ST3768

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
https://support.industry.siemens.com/cs/ww/en/ps/5ST3768

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)
https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5ST3768

CAx-Online-Generator
https://www.siemens.com/cax

Tender specifications
https://www.siemens.com/specifications

Kennlinien
https://curves.simaris.siemens.com/curves/5ST3768

---

last modified: 10/6/2026

Subject to change without notice
© Copyright Siemens

Subject to change without notice
© Copyright Siemens