SIEMENS

Data sheet 3TK2850-1AL20

SIRIUS safety relay with contactor relay enabling circuits (EC) 230 V DC, 90 mm Screw terminal EC instantaneous: 3 NO EC delayed: 0 SC: 0 Autostart/monitored start Basic device Maximum achieved SIL: 2, PL: d

product brand name	SIRIUS
product designation	safety relays
design of the product	for EMERGENCY-STOP and safety doors
product type designation	3TK28
Product Function	
product function	
● automatic start	Yes
● light barrier monitoring	No
● standstill monitoring	No
● protective door monitoring	Yes
● magnetically operated switch monitoring NC-NO	No
● magnetically operated switch monitoring NC-NC	Yes
● rotation speed monitoring	No
● laser scanner monitoring	No
● light array monitoring	No
● EMERGENCY OFF function	Yes
● monitored start-up	Yes
● pressure-sensitive mat monitoring	No
product feature cross-circuit-proof	Yes
suitability for interaction press control	No
suitability for use	
● monitoring of floating sensors	Yes
● monitoring of non-floating sensors	No
● position switch monitoring	Yes
● EMERGENCY-OFF circuit monitoring	Yes
● valve monitoring	No
● opto-electronic protection device monitoring	No
● tactile sensor monitoring	No
● magnetically operated switch monitoring	No
● proximity switch monitoring	No
● safety-related circuits	Yes
General technical data	
certificate of suitability UL approval	Yes
insulation voltage rated value	690 V
surge voltage resistance rated value	6 000 V
protection class IP	
● of the enclosure	IP20
● of the terminal	IP20
shock resistance	5 g / 11 ms
vibration resistance according to IEC 60068-2-6	5 ... 500 Hz: 0,075 mm
operating frequency maximum	1 000 1/h
Substance Prohibitance (day/month/year)	05/01/2012
SVHC substance name	Lead monoxide (lead oxide) CAS-No. 1317-36-8 6,6'-di-tert-butyl-2,2'-methylenedi-p-cresol CAS-No. 119-47-1
Net Weight	0.689 kg
Ambient conditions	
installation altitude at height above sea level maximum	2 000 m
ambient temperature	
● during operation	-25 ... +60 °C

Subject to change without notice
© Copyright Siemens

● during storage	-40 ... +80 °C
relative humidity during operation	10 ... 95 %
air pressure according to SN 31205	90 ... 106 kPa
Electromagnetic compatibility	
installation environment regarding EMC	This product is suitable for Class A environments only. In household environments, this device can cause unwanted radio interference. The user is required to implement appropriate measures in this case.
EMC emitted interference	IEC 60947-5-1, IEC 60000-4-3, IEC 60000-4-5, IEC 60000-4-6
Safety related data	
product function suitable for safety function	Yes
stop category according to IEC 60204-1	0
IEC 62061	
SIL Claim Limit (subsystem) according to EN 62061	2
PFHD with high demand rate according to IEC 62061	1.2E-8 1/h
ISO 13849	
category according to EN ISO 13849-1	3
IEC 61508	
Safety Integrity Level (SIL)	
● according to IEC 61508	2
safety device type according to IEC 61508-2	Type B
hardware fault tolerance according to IEC 61508	1
T1 value for proof test interval or service life according to IEC 61508	20 a
Electrical Safety	
touch protection against electrical shock	finger-safe
Short-circuit protection	
design of the fuse link for short-circuit protection of the NO contacts of the relay outputs required	gL/gG: 10 A
Inputs	
design of input	
● cascading input/functional switching	No
● feedback input	Yes
● start input	Yes
number of sensor inputs	
● 1-channel or 2-channel	1
Outputs	
number of outputs as contact-affected switching element	
● as NC contact	
— for signaling function instantaneous contact	0
● as NO contact	
— safety-related instantaneous contact	3
— safety-related delayed switching	0
mechanical service life (operating cycles) typical	30 000 000
number of outputs as contact-less semiconductor switching element	
● for signaling function	
— delayed switching	0
— instantaneous contact	0
● safety-related	
— delayed switching	0
— instantaneous contact	0
switching capacity current of the NO contacts of the relay outputs at DC-13	
● at 24 V	10 A
● at 115 V	1 A
● at 230 V	0.3 A
switching capacity current of the NO contacts of the relay outputs at AC-15	
● at 115 V	6 A
● at 230 V	6 A
switching capacity current of the NC contacts of the relay	

© Copyright Siemens

outputs at DC-13	
● at 24 V	10 A
● at 115 V	1 A
● at 230 V	0.3 A
switching capacity current of the NC contacts of the relay outputs at AC-15	
● at 115 V	6 A
● at 230 V	6 A
wire length between sensor and electronics evaluation device with Cu 1.5 mm² and 150 nF/km maximum	2 000 m
Times	
make time with automatic start	
● typical	100 ms
● at AC maximum	200 ms
make time with automatic start after power failure	
● typical	350 ms
● maximum	500 ms
make time with monitored start	
● typical	60 ms
● maximum	100 ms
backslide delay time after opening of the safety circuits typical	30 ms
backslide delay time in the event of power failure	
● typical	100 ms
● maximum	120 ms
recovery time after opening of the safety circuits typical	20 ms
recovery time after power failure typical	0.02 s
pulse duration	
● of the sensor input minimum	20 ms
● of the ON pushbutton input minimum	0.02 s
● of the cascading input minimum	0.02 s
Control circuit/ Control	
type of voltage of the control supply voltage	AC
control supply voltage 1 at AC	
● at 50 Hz rated value	230 V
● at 60 Hz rated value	230 V
control supply voltage frequency	
● 1 rated value	50 Hz
● 2 rated value	60 Hz
operating range factor control supply voltage rated value of magnet coil at AC	
● at 50 Hz	0.9 ... 1.15
● at 60 Hz	0.9 ... 1.15
Installation/ mounting/ dimensions	
mounting position	any
fastening method	screw and snap-on mounting
height	132 mm
width	90 mm
depth	108 mm
Connections/ Terminals	
type of electrical connection	screw terminal
type of connectable conductor cross-sections	
● solid	1x (0.2 ... 2.5 mm²), 2x (0.2 ... 1.0 mm²)
● finely stranded with core end processing	1x (0.25 ... 2.5 mm²), 2x (0.25 ... 1.0 mm²)
● for AWG cables solid	2x (24 ... 18)
● for AWG cables stranded	2x (24 ... 18)
connectable conductor cross-section	
● solid	0.2 ... 2.5 mm²
● finely stranded with core end processing	0.25 ... 2.5 mm²
AWG number as coded connectable conductor cross	

© Copyright Siemens

section	
● solid	24 ... 18
● stranded	24 ... 18
DC resistance of the cable maximum	250 Ω
type of electrical connection plug-in socket	Yes

Approvals Certificates


Environment	General Product Approval			EMV	Functional Saftey
Environmental Confirmations	CCC	UL	EAC	RCM	Type Examination Certificate

Test Certificates	other	
Special Test Certificate	Confirmation	产品合格 QC PASS

Further information

Information on the packaging
https://support.industry.siemens.com/cs/ww/en/view/109813875
Information for data generation and storage
https://support.industry.siemens.com/cs/ww/en/view/109995012
Information- and Downloadcenter (Catalogs, Brochures,…)
https://www.siemens.com/ic10
Industry Mall (Online ordering system)
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3TK2850-1AL20
Cax online generator
https://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3TK2850-1AL20
Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
https://support.industry.siemens.com/cs/ww/en/ps/3TK2850-1AL20
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)
https://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3TK2850-1AL20&lang=en

Subject to change without notice
© Copyright Siemens



last modified: 7/31/2026

Subject to change without notice
© Copyright Siemens