SIEMENS

Data sheet 3RS1700-1AD00



interface converter Phased-out product !!! For further information, please contact our sales department 24 V AC/DC, 2-way separation input: 0-10 V output: 0-10 V screw terminal

product brand name	SIRIUS
product designation	single interface converter
General technical data	
design of the base unit	active
number of channels	1
consumed active power	0.3 W
insulation voltage for overvoltage category III according to IEC 60664 with degree of pollution 2 rated value	50 V
shock resistance according to IEC 60068-2-27	15 g / 11 ms
vibration resistance according to IEC 60068-2-6	10 ... 55 Hz: 0.35 mm
reference code according to IEC 81346-2	T
Substance Prohibitance (day/month/year)	07/01/2006
Net Weight	0.055 kg
Supply voltage	
supply voltage at AC	
● at 50 Hz rated value	24 V
● at 60 Hz rated value	24 V
supply voltage at DC rated value	24 V
supply voltage frequency rated value	60 ... 50 Hz
operating range factor supply voltage rated value	
● at AC at 50 Hz	0.8 ... 1.2
● at AC at 60 Hz	0.8 ... 1.2
● at DC	0.7 ... 1.25
Precision	
relative metering precision	0.1 %
relative linearity deviation	0.02 %
temperature drift per °C	0.015 %/°C
voltage ripple maximum	5 mV
limit frequency	30 Hz
settling time for 1 % deviation	30 ms
rise time	10 ms
Main circuit	
type of voltage	AC/DC
Inputs/ Outputs	
input voltage maximum	30 V
property of the output short-circuit proof	Yes
overvoltage strength at the current output maximum	30 V
type of signal at input	0 ... 10 V
type of signal at output	0 ... 10 V

Subject to change without notice
© Copyright Siemens

output load	
● at voltage output maximum	1 kΩ
Galvanic isolation	
design of the electrical isolation	2 paths
galvanic isolation	
● between input and output	Yes
● between the voltage supply and other circuits	No
Connections/ Terminals	
type of electrical connection	screw terminal
type of connectable conductor cross-sections	
● solid	1x (0.5 ... 2.5 mm²)
● finely stranded with core end processing	2x (0.5 ... 2.5 mm²)
● for AWG cables stranded	1x (20 ... 14)
connectable conductor cross-section	
● solid	0.5 ... 2.5 mm²
● finely stranded with core end processing	0.5 ... 2.5 mm²
AWG number as coded connectable conductor cross section	
● solid	20 ... 14
● stranded	20 ... 14
tightening torque with screw-type terminals	0.5 ... 0.8 N·m
Installation/ mounting/ dimensions	
mounting position	any
fastening method	snap-on mounting on 35 mm DIN rail according to DIN EN 50022
height	79 mm
width	6.2 mm
depth	84 mm
Ambient conditions	
ambient temperature	
● during operation	-25 ... +60 °C
● during storage	-40 ... +85 °C
● during transport	-40 ... +85 °C

Approvals Certificates

Environment	General Product Approval	EMV	Test Certificates	other
Environmental Confirmations			Type Test Certificates/Test Report	Confirmation


other

产品合格
QC PASS

Further information

Information on the packaging
https://support.industry.siemens.com/cs/ww/en/view/109813875
Information for data generation and storage
https://support.industry.siemens.com/cs/ww/en/view/109995012
Information- and Downloadcenter (Catalogs, Brochures,…)
https://www.siemens.com/ic10
Industry Mall (Online ordering system)
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RS1700-1AD00
Cax online generator
https://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RS1700-1AD00
Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
https://support.industry.siemens.com/cs/ww/en/ps/3RS1700-1AD00
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)
https://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RS1700-1AD00&lang=en

Subject to change without notice
© Copyright Siemens



last modified: 4/4/2026

Subject to change without notice
© Copyright Siemens