SIEMENS

## Data sheet 6AG4131-2GG40-0BX6

SIMATIC IPC627D (Box PC), HD graphic onboard, 2x Gigabit Ethernet (IE/PN) 4xUSB V3.0; 1x serial (COM 1); RAID controller onboard; Watchdog, temp./fan monitoring XEON E3-1268LV3 (4C/8T, 2.3 (3.3) GHz, 8 MB cache VT-D, AMT) RAID1 2x 320 GB SATA (2.5") 16 GB DDR3 1600 DIMM; 2x PCI without expansion (HW) Windows 7 Ultimate 64 bit SP1, MUI (de, en, fr, es, it) without expansion (software) 24 V DC industrial Power supply

| | |
|---|---|
| **General information** | |
| Product type designation | IPC627D |
| **Installation type/mounting** | |
| Mounting | Wall mounting, portrait mounting |
| Design | Box PC, built-in unit |
| **Supply voltage** | |
| Type of supply voltage | 100/240 V AC (autorange); 24 V DC |
| Line frequency | |
| ● Rated value 50 Hz | Yes |
| ● Rated value 60 Hz | Yes |
| Mains buffering | |
| ● Mains/voltage failure stored energy time | 20 ms |
| **Processor** | |
| Processor type | Celeron G1820TE (2C/2T, 2.2 GHz, 2 MB Cache); Core i3-4330TE (2C/4T, 2.4 GHz, 4 MB Cache); Xeon E3-1268L v3 (4C/8T, 2.3 (3.3) GHz, 8 MB Cache, AMT) |
| Chipset | Intel DH82C226 PCH |
| **Graphic** | |
| Graphics controller | Intel HD graphics controller P4600 GT2 (Xeon, Core i3); Intel HD graphics controller (Celeron) |
| **Drives** | |
| Optical drives | DVD±R±RW combi-drive, optional |
| Hard disk | 3.5" SATA ≥ 500 GB, optional: 3.5" SATA ≥ 1 TB; RAID1 2x 2.5" SATA ≥ 320 GB; solid-state drive (SSD) ≥ 240 GB; all hard disk drives within the enclosure are vibration-damped; RAID1 2x 2.5" SATA ≥ 320 GB byte in removable drive bay |
| SSD | Yes; ≥ 240 GB optional |
| **Storage** | |
| Type of memory | DDR3-1600 DIMM |
| Main memory | 2 / 4 / 8 / 16 GB; ECC optional |
| Capacity of main memory, max. | 16 Gbyte |
| **Data areas and their retentivity** | |
| Retentive data area (incl. timers, counters, flags), max. | 2 Mbyte; 128 KB can be stored in the buffer time; optional |
| **Hardware configuration** | |
| Slots | |
| ● Number of PCI slots | 2; Optional |
| ● Number of PCI slots | 2; Optional |
| **Interfaces** | |
| Number of industrial Ethernet interfaces | 2; 2x RJ45 (independent) |
| Number of PROFINET interfaces | 3; Optional |
| serial interface | 1x COM1 (RS 232), optional: 1x COM2 (RS 232) |
| Video interfaces | |
| ● Graphics interface | 1x DisplayPort and 1x DVI-I; 1x VGA via adapter cable (optional) |
| Industrial Ethernet | |
| ● Industrial Ethernet interface | |
| — 100 Mbps | Yes |
| — 1000 Mbps | Yes |
| **Interrupts/diagnostics/status information** | |


Subject to change without notice
© Copyright Siemens

| | |
|---|---|
| LED status display | Yes |
| Bus diagnostics | Yes |
| **Integrated Functions** | |
| Monitoring functions | |
| ● Temperature monitoring | Yes |
| ● Fan | Yes |
| ● Monitoring function via network | Optional |
| **Degree and class of protection** | |
| IP degree of protection | IP20 |
| IP (at the front) | IP20 |
| IP (rear) | IP20 |
| **Standards, approvals, certificates** | |
| CE mark | Yes |
| UL approval | Yes |
| ● UL 508 | Yes |
| cULus | Yes |
| RCM (formerly C-TICK) | Yes |
| KC approval | Yes |
| FCC | Yes |
| Marine approval | |
| ● Germanischer Lloyd (GL) | Yes |
| ● American Bureau of Shipping (ABS) | Yes |
| ● Bureau Veritas (BV) | Yes |
| ● Det Norske Veritas (DNV) | Yes |
| ● Lloyds Register of Shipping (LRS) | Yes |
| ● Nippon Kaiji Kyokai (Class NK) | Yes |
| **Ambient conditions** | |
| Ambient temperature during operation | |
| ● min. | 5 °C |
| ● max. | 55 °C |
| Ambient temperature during storage/transportation | |
| ● min. | -20 °C |
| ● max. | 60 °C |
| Vibrations | |
| ● Vibration resistance during operation acc. to IEC 60068-2-6 | tested according to DIN IEC 60068-2-6: 10 Hz to 58 Hz: 0.075 mm; 58 Hz to 500 Hz 9.8 m/s² (1 g) |
| **Operating systems** | |
| pre-installed operating system | Windows 7 Ultimate, 32-bit/64-bit, MUI; Windows Embedded Standard 7 P, 32-bit, MUI; Windows 10 Enterprise 2015 or 2016 LTSB, 64-bit, MUI |
| without operating system | Yes |
| pre-installed operating system | |
| ● Windows 7 | Yes; Ultimate 32 bit or 64 bit |
| ● Windows 10 Enterprise | Yes; Windows 10 Enterprise 2015 or 2016 LTSB, 64-bit, MUI |
| **Dimensions** | |
| Width | 312 mm |
| Height | 81 mm; with DVD drive: 105 mm |
| Depth | 301 mm; incl. mounting rail |
| **Approvals / Certificates** | |
| **General Product Approval** | |

Miscellaneous







Manufacturer Declaration






| |
|---|
| **General Product Approval** |


© Copyright Siemens

| | | | | | |
|---|---|---|---|---|---|
| RCM | EAC | BIS CRS | Manufacturer Declaration | China RoHS | EG-Konf. |

| General Product Approval | Maritime application | | | | |
|---|---|---|---|---|---|
| UKCA | ABS | BUREAU VERITAS | DNV | Lloyd's Register LRS | NK / Nippon Kaiji Kyokai |

| Maritime application | | other | Dangerous goods | | |
|---|---|---|---|---|---|
| CCS (China Classification Society) | KR (Korean Register of Shipping) | CB | Dangerous goods information | Test Summary Report UN 38.3 | Dangerous goods information |

| Dangerous goods | Environment | |
|---|---|---|
| Test Summary Report UN 38.3 | Environmental Confirmations | Environmental Confirmations |

**last modified:** 6/10/2026


Subject to change without notice
© Copyright Siemens