SIEMENS

Data sheet for SINAMICS G150

Article No. : 6SL3710-2GE41-1AA3



Figure similar

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Rated data


Input		
Supply frequency	47...63 Hz	
Supply voltage	400 V ±10 %	
Rated input current	1,174 A	
Max. current	1,800 A	
Pulse number	12	
Energy recovery capability	No	(2Q)
Output		
Output voltage	400 V	
Rated power (LO) in kW	630 kW	
Rated power (HO) in kW	500 kW	
Rated output current	1,120 A	
Rated output current (LO)	1,092 A	
Rated output current (HO)	850 A	
Output current Max	0 A	
Pulse frequency (factory setting)	1.25 kHz	
Basic data		
Power losses ΔP	15.7 kW	
Power loss including options	15.7 kW	
Sound pressure level L_{pA} (1 m)	73 dB	
Conductor cross section, max. (IEC)	4 x 240 mm²	
Degree of protection	IP20	
Dimensions (H x W x D)	2,000 mm x 2,400 mm x 600 mm	
Weight approx.	1,700 kg	
Frame size	HX	
Design	A	
Color, paint shade	RAL7035	

Environmental conditions

Installation altitude	1,000 m
Coolant	Air
Coolant requirement, air	1.56 m³/s
Ambient temperature	0 °C - +40 °C

Converter losses to IEC61800-9-2*

Efficiency class	IE2
Comparison with the reference converter (90% / 100%)	49.5 %



The percentage values show the losses in relation to the rated apparent power of the converter.

The diagram shows the losses for the points (as per standard IEC61800-9-2) of the relative torque generating current (I) over the relative motor stator frequency(f). The values are valid for the basic version of the converter including line choke without options/components.

*calculated values