SIEMENS

## Data sheet for SIMOTICS S-1FK7

**Article No. :** **1FK7063-5AH71-1FH3**



Figure similar

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

| Engineering data | |
|---|---|
| Rated speed (100 K) | 4,500 rpm |
| Number of poles | 8 |
| Rated torque (100 K) | 3.0 Nm |
| Rated current | 3.8 A |
| Static torque (60 K) | 9.10 Nm |
| Static torque (100 K) | 11.00 Nm |
| Stall current (60 K) | 9.90 A |
| Stall current (100 K) | 12.00 A |
| Moment of inertia | 17.300 kgcm² |
| Efficiency | 90.0 % |

| Physical constants | |
|---|---|
| Torque constant | 0.91 Nm/A |
| Voltage constant at 20° C | 58.0 V/1000*min⁻¹ |
| Winding resistance at 20° C | 0.29 Ω |
| Rotating field inductance | 3.2 mH |
| Electrical time constant | 11.00 ms |
| Mechanical time constant | 1.58 ms |
| Thermal time constant | 40 min |
| Shaft torsional stiffness | 35,000 Nm/rad |
| Net weight of the motor | 12.0 kg |

| Mechanical data | |
|---|---|
| Motor type | Permanent-magnet synchronous motor |
| Motor type | Compact |
| Shaft height | 63 |
| Cooling | Natural cooling |
| Radial runout tolerance | 0.040 mm |
| Concentricity tolerance | 0.10 mm |
| Axial runout tolerance | 0.10 mm |
| Vibration severity grade | Grade A |
| Connector size | M23 |
| Degree of protection | IP64 |
| Design acc. to Code I | IM B5 (IM V1, IM V3) |
| Temperature monitoring | KTY84 temperature sensor in the stator winding |
| Electrical connectors | Connectors for signals and power rotatable |
| Color of the housing | Standard (Anthracite RAL 7016) |
| Holding brake | with holding brake |
| Shaft end | Plain shaft |
| Encoder system | Encoder AM22DQ: absolute encoder 22 bits (resolution 4194304, encoder-internal 2048 S/R) + 12 bits multi-turn (traversing range 4096 revolutions) |

| Optimum operating point | |
|---|---|
| Optimum speed | 3,300 rpm |
| Optimum power | 2.3 kW |

| Limiting data | |
|---|---|
| Max. permissible speed (mech.) | 7,200 rpm |
| Max. permissible speed (inverter) | 9,900 rpm |
| Maximum torque | 35.0 Nm |
| Maximum current | 42.0 A |

| Holding brake | |
|---|---|
| Holding brake version | Permanent-magnet brake |
| Holding torque | 13.0 Nm |
| Power supply voltage | DC 24 V ± 10 % |
| Coil current | 0.8 A |
| Opening time | 100 ms |
| Closing time | 50 ms |
| Highest braking work | 380 J |

| Recommended Motor Module | |
|---|---|
| Rated inverter current | 18 A |
| Maximum inverter current | 36 A |
| Maximum torque | 31.20 Nm |

Subject to change. Calculated values may differ from nameplate ratings. © Copyright Siemens