SIEMENS

Data sheet 6ES7408-1TA01-0XA0

********** spare part ********* SIMATIC S7-400, fan subassembly for rack with 18 slots, 24 V DC



Figure similar

Supply voltage	
Rated value (DC)	
● 24 V DC	Yes
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	30 V
Input current	
Inrush current, typ.	0.9 A; at 24 V
Power loss	
Power loss, max.	11 W
Digital outputs	
Relay outputs	
● Rated supply voltage of relay coil L+ (DC)	24 V
Switching capacity of contacts	
— with resistive load, max.	200 mA
Dimensions	
Width	482.5 mm
Height	109.5 mm
Depth	235 mm
Weights	
Weight, approx.	1 600 g
Classifications	

	Version	Classification
eClass	16	27-24-22-92
eClass	14	27-24-22-92
eClass	12	27-24-22-92
eClass	9.1	27-24-22-92
eClass	9	27-24-22-92
eClass	8	27-24-92-90
eClass	7.1	27-24-92-90
eClass	6	27-24-92-90
ETIM	10	EC002584
ETIM	9	EC002584
ETIM	8	EC002584
ETIM	7	EC002584
IDEA	4	3552

Subject to change without notice
© Copyright Siemens

	UNSPSC	15	32-15-17-03

Approvals / Certificates

General Product Approval

Miscellaneous











General Product Approval			EMV		Maritime application
China RoHS	Miscellaneous	Manufacturer Declaration			







Maritime application







CCS (China Classification Society)

last modified: 7/16/2026

Subject to change without notice
© Copyright Siemens