SIEMENS

Data sheet for SINUMERIK Electronic handwheel



Figure similar

Article No. : 6FC9320-5DE02

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Rated data	
Input voltage	DC 5 V
Max. power consumption	60 mA
Interface	TTL / RS 422
Displacement angle, signal A to B	90 °
Pulses per revolution	100
Actuating force	0.04 Nm
Output frequency	2.00 kHz
Transmission link	
to NCU/PCU, max.	20 m (65.62 ft)
to PPU max.	20 m (65.62 ft)

Mechanical data	
Net weight	0.3 kg (0.66 lb) Without connecting cable
Width	85.0 mm (3.35 in)
Height	160.0 mm (6.30 in)
Depth	67.0 mm (2.64 in)
Degree of protection	IP65

Ambient conditions	
Climate class according to EN60721-3-3	Condensation and icing excluded. Low air temperature 0 °C (32 °F).
Ambient temperature	
Operation	0 ... 55 °C (32 ... 131 °F)
Transport	-40 ... 70 °C (-40 ... 158 °F)
Storage	-25 ... 55 °C (-13 ... 131 °F)
Relative humidity	
Operation	5 ... 95 %
Storage	5 ... 95 %
Transport	5 ... 95 %

Approvals	
Certificate of suitability	CE, cULus