SIEMENS

Data sheet for SIMOTICS M-1PH8



Figure similar

Article No. : **1PH8105-1AF12-0DA1**

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data

		P_N [kW]	M_N [Nm]	I_N [A]	U_N [V]	f_N [Hz]	n_N [rpm]	M_{max} [Nm]	I_{max} [A]	n_{max} [rpm]	M_0 [Nm]	I_0 [A]	η	cos φ	Iμ [A]
Y	**ALM 400V**	**8.0**	**44.0**	**17.5**	**400**	**60.2**	**1,750**	**103**	**41.0**	**9,000**	**52.0**	**20**	**0.878**	**0.780**	**8.8**
	BLM/SLM 400V	7.0	45.0	17.5	348	51.9	1,500	103	41.0	9,000	52.0	20	0.867	0.790	8.8
	ALM 480V	9.9	43.0	17.0	485	75.3	2,200	103	41.0	9,000	52.0	20	0.900	0.790	8.7
	BLM/SLM 480V	9.0	43.0	17.0	453	68.5	2,000	103	41.0	9,000	52.0	20	0.911	0.780	8.7

Mechanical data

Motor type	Squirrel cage asynchronous motor
Shaft height	100
Cooling	Forced ventilation NDE -> DE
Vibration severity grade	SR/A
Shaft and flange accuracy	R
Degree of protection	IP55
Design acc. to Code I	IM B5 (IM V1, IM V3)
Temperature monitoring	KTY84 temperature sensor in the stator winding
Color	Standard (Anthracite RAL 7016)
Type of the bearing	Standard with fixed bearing
Shaft end	Plain shaft
Encoder system	Without encoder

Physical constants

Thermal time constant	20 min
Moment of inertia	252 kgcm²
Weight (approx.)	65 kg

Connection

Type of electrical connection	Terminal box
Position of the connection	NDE top
Power connection	right
Signal connection	DE
Terminal box designation	gk813

Cooling data and sound pressure level

Airflow, min.	0.04 m³/s
Sound pressure level LpA(1m) motor + external fan operation 50 HZ rated load, tolerance + 3dB	70 dB [1]
Air discharge	axial
Pressure drop	110 Pa

External fan

Max. power consumption

3 AC 400 V / 50 Hz (±10%)	0.08 A
3 AC 400 V / 60 Hz (±10%)	0.07 A
3 AC 480 V / 60 Hz (±10%)	0.11 A

[1] at a rated frequency of 4 kHz and a speed range of up to 5000 rpm

Subject to change. Calculated values may differ from nameplate ratings. © Copyright Siemens