SIEMENS

Data sheet 3NE1332-4D



PV fuse link, with blade contacts, NH2L, In: 400 A, gPV, Un DC: 1000 V, front indicator

Model	
product brand name	SENTRON
product designation	PV fuse link
design of the product	with blade contacts without slots
design of an identification indicator	front indicator
design of the switching contact	with blade contacts
design of the fuse link	Photovoltaic fuse, LV HRC design
General technical data	
size of fuse system according to EN 60269-1	NH2L
operating class of the fuse link	gPV
varying load factor (WL)	1
type of voltage of the operating voltage	DC
Supply voltage	
supply voltage	
● at DC	1 000 V
Breaking Capacity	
switching capacity current	
● at DC according to IEC 60947-2 rated value	30 kA
Dissipation	
power loss [W]	82 W
power loss [W]	
● for rated value of the current at AC in hot operating state per pole	82 W
● maximum	82 W
Product details	
product description	non-corroding, silver-plated
accessories included	no
Mechanical Design	
mounting position	Any, preferably vertical
Net Weight	1.097 kg
Environmental conditions	
ambient temperature during operation	
● minimum	-20 °C
● maximum	50 °C
environmental category	-20 to +50 at 95% relative humidity
Approvals Certificates	

Environment	General Product Approval

Subject to change without notice
© Copyright Siemens

Environmental Confirmations

Environmental Confirmations

Confirmation

General Product Approval	Test Certificates	other		
	Special Test Certificate	Miscellaneous	Confirmation	

Further information

Information on the packaging
https://support.industry.siemens.com/cs/ww/en/view/109813875
Information for data generation and storage
https://support.industry.siemens.com/cs/ww/en/view/109995012
Information- and Downloadcenter (Catalogs, Brochures,…)
https://www.siemens.com/lowvoltage/catalogs
Industry Mall (Online ordering system)
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3NE1332-4D
Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
https://support.industry.siemens.com/cs/ww/en/ps/3NE1332-4D
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)
https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NE1332-4D
CAx-Online-Generator
https://www.siemens.com/cax
Tender specifications
https://www.siemens.com/specifications
Kennlinien
https://curves.simaris.siemens.com/curves/3NE1332-4D

last modified: 4/4/2025

Subject to change without notice
© Copyright Siemens

Subject to change without notice
© Copyright Siemens