SIEMENS

Data sheet 5SM2647-0



Figure similar

RC unit, 4-pole, type AC, In: 100 A, 300 mA, Un AC: 400 V, for 5SP4

Model	
product brand name	SENTRON
product designation	RCD-unit
design of the product	Instantaneous
product type designation	5SM2
product version	for 5SP4
General technical data	
number of poles	4
design of pole	4 poles
size of installation devices according to DIN 43880	1
touch protection against electrical shock according to EN 50274	Finger and back-of-hand safe
mechanical service life (operating cycles) typical	10 000
overvoltage category	III
degree of pollution	2
Voltage	
type of voltage of the operating voltage	AC
insulation voltage (Ui) rated value	460 V
surge voltage resistance rated value	4 000 V
tripping fault current rated value	300 mA
• operational current	
— at 40 °C rated value	93 A
— at 45 °C rated value	93 A
— at 50 °C rated value	90 A
— at 55 °C rated value	87 A
— at 60 °C rated value	85 A
— at 65 °C rated value	83 A
— at 70 °C rated value	80 A
• operational current at AC rated value	100 A
residual current type	AC
supply voltage	
• at AC	400 V
• for testing equipment minimum	195 V
value range of the supply voltage frequency	50 Hz
value range of the operating frequency	50 Hz
Protection class	
protection class IP	IP20, if the distribution board is installed, with connected conductors

Subject to change without notice
© Copyright Siemens

protection function false tripping	Yes
Dissipation	
power loss [W]	
• for rated value of the current at AC in hot operating state per pole	5 W
• maximum	15 W
Product details	
product feature OFF-delay time adjustable	No
product feature rated fault current adjustable	No
product feature sealable	No
Connections	
connectable conductor cross-section solid	
• minimum	6 mm²
• maximum	50 mm²
connectable conductor cross-section stranded	
• minimum	6 mm²
• maximum	50 mm²
tightening torque with screw-type terminals	
• minimum	2.5 N·m
• maximum	3 N·m
position of power supply cord	top or bottom
Mechanical Design	
height	90 mm
width	124 mm
depth	70 mm
installation depth	70 mm
number of modular width units	5
fastening method	DIN-rail mounting
mounting position	any
Net Weight	711 g
Environmental conditions	
ambient temperature during operation	
• minimum	-25 °C
• maximum	45 °C
ambient temperature during storage	
• minimum	-40 °C
• maximum	75 °C
number of test cycles for environmental testing according to IEC 60068-2-30	28
Certificates	
reference code according to IEC 81346-2	F

Approvals Certificates

Environment		General Product Approval		
Environmental Confirmations	Environmental Confirmations		Miscellaneous	Miscellaneous

General Product Approval			other	Dangerous goods
Confirmation			Confirmation	Transport Information

Further information

Information on the packaging
https://support.industry.siemens.com/cs/ww/en/view/109813875
Information for data generation and storage

Subject to change without notice
© Copyright Siemens

https://support.industry.siemens.com/cs/ww/en/view/109995012

Information- and Downloadcenter (Catalogs, Brochures,…)
https://www.siemens.com/lowvoltage/catalogs

Industry Mall (Online ordering system)
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5SM2647-0


Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
https://support.industry.siemens.com/cs/ww/en/ps/5SM2647-0

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)
https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SM2647-0

CAx-Online-Generator
https://www.siemens.com/cax

Tender specifications
https://www.siemens.com/specifications

Kennlinien
https://curves.simaris.siemens.com/curves/5SM2647-0



last modified: 10/22/2026

Subject to change without notice
© Copyright Siemens

Subject to change without notice
© Copyright Siemens