SIEMENS

Data sheet 6GK5532-2SR00-2RR3

SCALANCE XR524-8WG; managed IE switch, 19" rack; 24x 10/100/1000 Mbps RJ45 port; 8x 1G/10G SFP+ port; no UL/FM approval; LED diagnostics; select/set button; PROFINET IO device, network management, integrated redundancy manager, office features (RSTP, VLAN, IGMP,..) CLP not included in scope of delivery; power supply 24 V DC; layer 3 integrated; layer 3 integrated;



product type designation	
product brand name	SCALANCE
product type designation	XR524-8WG
Technical Product Detail Page	https://i.siemens.com/1P6GK5532-2SR00-2RR3
transfer rate	
transfer rate	10, 100, 1000 Mbit/s
transfer rate	10 Gbit/s
interfaces / for communication / integrated	
number of electrical connections	
● for network components or terminal equipment	32
number of 10/100/1000 Mbit/s RJ45 ports	24; RJ45
number of electrical connections	
● for SFP+	8
interfaces / other	
number of electrical connections	
● for operator console	1
● for power supply	2
type of electrical connection	
● for operator console	USB (2.0 type B, USB-to-serial adapter)
● for power supply	2 x 2-pole terminal block
design of the removable storage	
● CLP	Yes
supply voltage, current consumption, power loss	
product component / connection for redundant voltage supply	Yes
type of voltage supply / redundant power supply unit	No
type of voltage / 1 / of the supply voltage	DC
● supply voltage / 1 / rated value	24 V
● power loss [W] / 1 / rated value	72 W
● supply voltage / 1 / voltage range	19.2 ... 31.2
● consumed current / 1 / maximum	3 A
● type of electrical connection / 1 / for power supply	2 x 2-pole terminal block
● product component / 1 / fusing at power supply input	Yes
● fuse protection type / 1 / at input for supply voltage	F 10 A / 250 V
type of voltage / 2 / of the supply voltage	AC (50 / 60 Hz)
● supply voltage / 2 / rated value	24 V
● power loss [W] / 2 / rated value	72 W
● supply voltage / 2 / voltage range	19.2 ... 30
● consumed current / 2 / maximum	3 A
● type of electrical connection / 2 / for power supply	2 x 2-pole terminal block

Subject to change without notice
© Copyright Siemens

● fuse protection type / 2 / at input for supply voltage	F 10 A / 250 V
ambient conditions	
ambient temperature / in horizontal mounting position / during operation	0 ... 60 °C
installation altitude / at height above sea level / maximum	4000 m
relative humidity	
● at 25 °C / without condensation / during operation / maximum	95 %
protection class IP	IP20
design, dimensions and weights	
design	19-inch rack
number of modular height units / relating to 19-inch cabinet	1
width	446 mm
height	43.6 mm
depth	374.8 mm
net weight	8 kg
material / of the enclosure	metal
fastening method	
● 19-inch installation	Yes
product features, product functions, product components / general	
cascading in the case of a redundant ring / at reconfiguration time of <\~0.3\~s	50
cascading in cases of star topology	any (depending only on signal propagation time)
number of automatically learnable MAC addresses	16382
number of QoS queues / per port	8
product function	
● QoS according to IEEE 802.1Q	Yes
product feature	
● Store & Forward switching method	Yes
product functions / management, configuration, engineering	
product function	
● CLI	Yes
● web-based management	Yes
● MIB support	Yes
● TRAPs via email	Yes
● configuration with STEP 7	Yes
● RMON	Yes
● port mirroring	Yes
● multiport mirroring	Yes
● CoS	Yes
● PROFINET IO diagnosis	Yes
● switch-managed	Yes
PROFINET conformity class	B
network load class / according to PROFINET	III
telegram length / for Ethernet / maximum	9194 byte
protocol / is supported	
● Telnet	Yes
● HTTP	Yes
● HTTPS	Yes
● TFTP	Yes
● FTP	Yes
● SFTP	Yes
● BOOTP	Yes
● NETCONF	No
● GMRP	Yes
● DCP	Yes
● LLDP	Yes
● EtherNet/IP	Yes
● SNMP v1	Yes
● SNMP v2	Yes

© Copyright Siemens

● SNMP v3	Yes
● IGMP (snooping/querier)	Yes
identification & maintenance function	
● I&M0 - device-specific information	Yes
● I&M1 - higher level designation/location designation	Yes
product functions / diagnostics	
product function	
● port diagnostics	Yes
● statistics Packet Size	Yes
● statistics packet type	Yes
● error statistics	Yes
● SysLog	Yes
product functions / VLAN	
product function	
● VLAN - port based	Yes
● VLAN - protocol-based	Yes
● VLAN - IP-based	Yes
● VLAN dynamic	Yes
number of VLANs / maximum	257
number of VLANs - dynamic / maximum	257
number of VLANs / at ring redundancy (HRP; MRP; standby link)	257
product functions / DHCP	
product function	
● DHCP server	Yes
● DHCP client	Yes
● DHCP Option 82	Yes
● DHCP Option 66	Yes
● DHCP Option 67	Yes
product functions / routing	
service / routing / note	IP routing integrated
product function	
● static IP routing	Yes
● static IP routing IPv6	No
● dynamic IP routing	Yes
● dynamic IP routing IPv6	No
protocol / is supported	
● RIPv2	Yes
● RIPnG for IPv6	No
● OSPFv2	Yes
● OSPFv3 for IPv6	No
● VRRP	Yes
● VRRP for IPv6	No
product functions / redundancy	
protocol / is supported / Media Redundancy Protocol (MRP)	Yes
product function	
● media redundancy protocol (MRP) with redundancy manager	Yes
● Media Redundancy Protocol Interconnection (MRP-I)	Yes; LC mode
● of the PROFINET IO device / is supported / PROFINET system redundancy	Yes
● ring redundancy	Yes
● high speed redundancy protocol (HRP) with redundancy manager	Yes
● high speed redundancy protocol (HRP) with standby redundancy	Yes
● redundancy procedure STP	Yes
● redundancy procedure RSTP	Yes
● redundancy procedure RSTP+	Yes
● redundancy procedure MSTP	Yes

© Copyright Siemens

● passive listening	Yes
protocol / is supported	
● STP/RSTP	Yes
● STP	Yes
● RSTP	Yes
● MSTP	Yes
● RSTP big network support	Yes
● LACP	Yes
system modification during operation	
product function / configuration in RUN via CiR/H-CiR	Yes
product functions / security	
product function	
● IEEE 802.1x (radius)	Yes
● broadcast/multicast/unicast limiter	Yes
● broadcast blocking	Yes
protocol / is supported	
● SSH	Yes
● SSL	Yes
product functions / time	
product function	
● SICLOCK support	Yes
● NTP-client	Yes
● SNTP client	Yes
● IEEE 1588 v2 transparent forwarding	Yes
protocol / is supported	
● NTP	Yes
● SNTP	Yes
accuracy / at IEEE 1588 v2	
● not less than	100 ns
● typical	50 ns
standards, specifications, approvals	
certificate of suitability	
● CE marking	Yes
● UKCA marking	Yes
● KC approval	Yes
● Regulatory Compliance Mark (RCM)	Yes
product conformity / according to EMC-guideline	2014/30/EU
standard	
● for EMC interference emission	EN 61000-6-4, EN 50121-9
● for immunity to EMC	EN 61000-6-2, EN 50121-4
standards, specifications, approvals / other	
certificate of suitability	
● RoHS conformity	Yes
resistance to air pollution / conformity according to ANSI/ISA-71.04	Yes; G3
IT security for industrial automation systems / according to IEC 62443-4-2:2019	Yes
standards, specifications, approvals / Environmental Product Declaration	
Environmental Product Declaration	Yes
global warming potential [CO2 eq]	
● total	2101.59 kg
● during manufacturing	132 kg
● during operation	1969 kg
● after end of life	0.59 kg
product functions / general	
MTBF	12.6 a
reference temperature / for MTBF determination	40 °C
warranty period	5 a
product function / is supported / identification link	Yes; acc. to IEC 61406-1:2022

Subject to change without notice
© Copyright Siemens

further information / internet links	
internet link	
● to website: Selection guide for cables and connectors	https://support.industry.siemens.com/cs/ww/en/view/109766358
● to web page: selection aid TIA Selection Tool	https://www.siemens.com/tstcloud
● to website: Industrial communication	https://www.siemens.com/simatic-net
● to web page: SiePortal	https://sieportal.siemens.com/
● to website: Image database	https://www.automation.siemens.com/bilddb
● to website: CAx-Download-Manager	https://www.siemens.com/cax
● to website: Industry Online Support	https://support.industry.siemens.com

security information	
security information	Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement - and continuously maintain - a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under https://www.siemens.com/cert. (V4.7)

Approvals / Certificates	
Environmental Product Declaration	
● global warming potential [CO2 eq] / during manufacturing	132 kg
● global warming potential [CO2 eq] / during operation	1969 kg
● global warming potential [CO2 eq] / after end of life	0.59 kg
● global warming potential [CO2 eq] / total	2101.59 kg

Environment	General Product Approval				Test Certificates
EPD	RCM	China RoHS	CE EG-Konf.	UK CA	Type Test Certificates/Test Report

last modified: 8/28/2026

Subject to change without notice
© Copyright Siemens