SIEMENS

Data sheet 6AG1332-4BA00-7AA0



Figure similar

SIPLUS S7-1500 PM 1507 24V/3A

SIPLUS S7-1500 PM 1507 24V/3A based on 6EP1332-4BA00 with conformal coating, -40…+70 °C, stabilized power supply input: 120/230 V AC output: 24 V DC/3 A

General information	
Technical Product Detail Page	https://i.siemens.com/1P6AG1332-4BA00-7AA0
product brand name	SIPLUS
product type designation	PM 1507
product designation	S7-1500 Power Module
type of current supply	24 V/3 A
manufacturer's article number of the basic version used for SIPLUS product versions	6EP1332-4BA00
input	
type of the power supply network	1-phase AC
phase number	1
voltage curve at input	AC
supply voltage at AC	Automatic range selection
supply voltage	120 V/230 V
input voltage 1 at AC	85 ... 132 V
input voltage 2 at AC	170 ... 264 V
supply voltage	
● at 50 Hz	230 V
● at 60 Hz	120 V
line frequency	50/60 Hz
line frequency	45 ... 65 Hz
wide range input	No
overvoltage overload capability	2.3 × Vin rated, 1.3 ms
buffering time for rated value of the output current in the event of power failure minimum	20 ms
operating condition of the mains buffering	at Vin = 93/187 V
input current	
● at rated input voltage 120 V	1.4 A
● at rated input voltage 230 V	0.8 A
current limitation of inrush current at 25 °C maximum	23 A
duration of inrush current limiting at 25 °C	
● maximum	3 ms
I2t value maximum	1.3 A²·s
fuse protection type	T 3,15 A/250 V (not accessible)
fuse protection type in the feeder	Recommended miniature circuit breaker: 10 A characteristic B or 6 A characteristic C
output	
voltage curve at output	Controlled, isolated DC voltage
product function output voltage controlled	Yes

Subject to change without notice
© Copyright Siemens

product function output voltage stabilized	Yes
output voltage at DC rated value	24 V
output voltage	
● at output 1 at DC rated value	24 V
output voltage	
● at output 1 at DC	24 V
output voltage adjustable	No
relative overall tolerance of the voltage	1 %
relative control precision of the output voltage	
● on slow fluctuation of input voltage	0.1 %
● on slow fluctuation of ohm loading	0.1 %
residual ripple	
● maximum	50 mV
voltage peak	
● maximum	150 mV
display version for normal operation	LED green for 24 V OK; LED red for error; LED yellow for stand-by
behavior of the output voltage when switching on	No overshoot of Vout (soft start)
response delay maximum	1.5 s
voltage increase time of the output voltage	
● typical	10 ms
output current	
● rated value	3 A
● rated range	0 ... 3 A
supplied active power typical	72 W
short-term overload current	
● on short-circuiting during the start-up typical	12 A
● at short-circuit during operation typical	12 A
duration of overloading capability for excess current	
● on short-circuiting during the start-up	70 ms
● at short-circuit during operation	70 ms
bridging of equipment	Yes
number of parallel-switched equipment resources for increasing the power	2
efficiency	
efficiency in percent	87 %
power loss [W]	
● at rated output voltage for rated value of the output current typical	11 W
closed-loop control	
relative control precision of the output voltage with rapid fluctuation of the input voltage by +/- 15% typical	0.1 %
relative control precision of the output voltage load step of resistive load 50/100/50 % typical	1 %
relative control precision of the output voltage at load step of resistive load 10/90/10 % typical	3 %
setting time	
● load step 10 to 90% typical	5 ms
● load step 90 to 10% typical	5 ms
● maximum	5 ms
protection and monitoring	
design of the overvoltage protection	Additional control loop, limitation (closed loop control) at < 28.8 V
property of the output short-circuit proof	Yes
design of short-circuit protection	Electronic shutdown, automatic restart
response value current limitation	3.15 ... 3.6 A
● typical	3.4 A
safety	
galvanic isolation between input and output	Yes
galvanic isolation	Output voltage: SELV, ES1 (IEC 62368-1), DVC As (IEC 61204-7)
operating resource protection class	Class I
leakage current	

Subject to change without notice
© Copyright Siemens

● maximum	3.5 mA
● typical	0.4 mA
protection class IP	IP20
EMC	
standard	
● for emitted interference	EN 55022 Class B
● for mains harmonics limitation	EN 61000-3-2
● for interference immunity	EN 61000-6-2
standards, specifications, approvals	
certificate of suitability	
● CE marking	Yes
● UKCA marking	Yes
MTBF at 40 °C	1 611 993 h
ambient conditions	
ambient temperature	
● in horizontal mounting position during operation	-40 ... +70 °C; with natural convection
● during transport	-40 ... +85 °C
● during storage	-40 ... +85 °C
installation altitude at height above sea level maximum	6 000 m
ambient condition relating to ambient temperature - air pressure - installation altitude	In case of operation at altitudes of 2000 - 6000 m above sea level: Output power derating of -7.5 %/1000 m or reduction of the ambient temperature by 5 K/1000 m
relative humidity with condensation according to IEC 60068-2-38 maximum	100 %; RH incl. condensation/frost (no commissioning if condensation is present), horizontal installation
chemical resistance to commercially available cooling lubricants	Yes; incl. diesel and oil droplets in the air
resistance to biologically active substances conformity according to EN 60721-3-3	Yes; Class 3B2 mold, fungal, sponge spores (except fauna); class 3B3 upon request
resistance to chemically active substances conformity according to EN 60721-3-3	Yes; Class 3C4 (RH < 75%) incl. salt spray acc. to EN 60068-2-52 (severity level 3)
resistance to mechanically active substances conformity according to EN 60721-3-3	Yes; Class 3S4 incl. sand, dust
resistance to biologically active substances conformity according to EN 60721-3-6	Yes; Class 6B2 mold, fungal, sponge spores (except fauna)
resistance to chemically active substances conformity according to EN 60721-3-6	Yes; Class 6C3 (RH < 75%) incl. salt spray acc. to EN 60068-2-52 (severity level 3)
resistance to mechanically active substances conformity according to EN 60721-3-6	Yes; Class 6S3 incl. sand, dust
coating for equipped printed circuit board according to EN 61086	Yes; Class 2 for high availability
type of coating protection against pollution according to EN 60664-3	Yes; Type 1 protection
type of test of the coating according to MIL-I-46058C	Yes; Discoloration of the coating during service life possible
product conformity of the coating Qualification and Performance of Electrical Insulating Compound for Printed Board Assemblies according to IPC-CC-830A	Yes; Conformal Coating, Class A
connection method	
type of electrical connection	Screw-/spring clamp connection
● at input	L, N, PE: 1 screw terminal each for 0.5 ... 2.5 mm²
● at output	L+, M: 2 spring-loaded terminals each for 0.5 to 2.5 mm²
removable terminal at input	Yes
removable terminal at output	Yes
mechanical data	
width × height × depth of the enclosure	50 × 147 × 129 mm
installation width × mounting height	50 mm × 205 mm
required spacing	
● top	40 mm
● bottom	40 mm
● left	0 mm
● right	0 mm
fastening method	Can be mounted onto S7-1500 rail
● DIN-rail mounting	No
● S7 rail mounting	Yes

Subject to change without notice
© Copyright Siemens

● wall mounting	No
housing can be lined up	Yes
net weight	0.45 kg
further information internet links	
internet link	
● to website: Industry Mall	https://mall.industry.siemens.com
● to website: Industry Online Support	https://support.industry.siemens.com
additional information	
other information	Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)
security information	
security information	Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement - and continuously maintain - a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under https://www.siemens.com/cert. (V4.7)

Classifications

	Version	Classification
eClass	16	27-04-07-01
eClass	14	27-04-07-01
eClass	12	27-04-07-01
eClass	9.1	27-04-07-01
eClass	9	27-04-07-01
eClass	8	27-04-90-02
eClass	7.1	27-04-90-02
eClass	6	27-04-90-02
ETIM	10	EC002540
ETIM	9	EC002540
ETIM	8	EC002540
ETIM	7	EC002540
IDEA	4	4130
UNSPSC	15	39-12-10-04

Approvals Certificates

General Product Approval

China RoHS | Manufacturer Declaration

General Product Approval	EMV	Maritime application
China RoHS		

Subject to change without notice
© Copyright Siemens

last modified: 5/5/2026

Subject to change without notice
© Copyright Siemens