SIEMENS

Data sheet 3VL6780-1SB36-0AA0

circuit breaker VL800N standard breaking capacity Icu=55kA, 415V AC 3-pole, line protection trip unit ETU10, LI In=800A, rated current IR=320...800A, overload protection, II=1.25 to 8 xIN, short-circuit protection without auxiliary release without auxiliary/alarm switch, spare part product only for replacement purposes

Weight	16.359 kg
Net Weight	16.359 kg

Approvals / Certificates

Environment		General Product Approval			
Environmental Confirmations	Environmental Confirmations	CCC	CSA	EAC	Confirmation

General Product Approval	Test Certificates	other			
UKCA	Special Test Certificate	Miscellaneous	产品合格 QC PASS	Confirmation	Miscellaneous

Dangerous goods

Transport Information

Further information

Information on the packaging
https://support.industry.siemens.com/cs/ww/en/view/109813875
Information for data generation and storage
https://support.industry.siemens.com/cs/ww/en/view/109995012
Information- and Downloadcenter (catalogues, leaflets,...)
https://www.siemens.com/energy-automation
Industry Mall (Online ordering system)
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VL6780-1SB36-0AA0
Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
https://support.industry.siemens.com/cs/ww/en/ps/3VL6780-1SB36-0AA0
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)
https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VL6780-1SB36-0AA0
CAx-Online-Generator
https://www.siemens.com/cax
Kennlinien
https://curves.simaris.siemens.com/curves/3VL6780-1SB36-0AA0

last modified: 11/24/2025

Subject to change without notice
© Copyright Siemens

Subject to change without notice
© Copyright Siemens