SIEMENS

Data sheet 3VL4740-1AA36-0AA0

circuit breaker VL400N without Electronic Trip Unit standard breaking capacity Icu=55kA/415V AC, 3-pole In=< 400A, rated current without auxiliary release with screw terminal connections for switching unit and Electronic Trip Unit

Weight	4.905 kg
Net Weight	4.557 kg

Approvals / Certificates

Environment		General Product Approval			
Environmental Confirmations	Environmental Confirmations			Confirmation	

Test Certificates	other		
Special Test Certificate	Miscellaneous	Confirmation	

Further information

Information on the packaging
https://support.industry.siemens.com/cs/ww/en/view/109813875
Information for data generation and storage
https://support.industry.siemens.com/cs/ww/en/view/109995012
Information- and Downloadcenter (catalogues, leaflets,...)
https://www.siemens.com/energy-automation
Industry Mall (Online ordering system)
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VL4740-1AA36-0AA0
Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
https://support.industry.siemens.com/cs/ww/en/ps/3VL4740-1AA36-0AA0
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)
https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VL4740-1AA36-0AA0
CAx-Online-Generator
https://www.siemens.com/cax
Kennlinien
https://curves.simaris.siemens.com/curves/3VL4740-1AA36-0AA0

last modified: 3/31/2025

Subject to change without notice
© Copyright Siemens

Subject to change without notice
© Copyright Siemens