SIEMENS

Data sheet for SINUMERIK Machine control panel MCP 398C



Figure similar

Article No. : 6FC5303-0AF25-0AA0

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Rated data	
Input voltage	DC 24 V
Power consumption, max.	29.3 W

Mechanical data	
Net weight	1.700 kg (3.75 lb)
Dimensions	
Width	398.0 mm (15.67 in)
Height	225.0 mm (8.86 in)
Depth	110.4 mm (4.35 in) With connector for handwheel connection
Installation depth	63.0 mm (2.48 in) With connector for handwheel connection clearance + 10 mm (0.39 in)
Mounting surface	
Cutout width	379.5 mm (14.94 in)
Cutout height	206.5 mm (8.13 in)
Degree of protection	
Rear side	IP00
Front side	IP54

Ambient conditions	
Climate class according to EN60721-3-3	Condensation and icing excluded. Low air temperature 0 °C (32 °F).
Ambient temperature	
Operation on the front	0 ... 45 °C (32 ... 113 °F)
Operation at the rear	0 ... 55 °C (32 ... 131 °F)
Transport	-40 ... 70 °C (-40 ... 158 °F)
Storage	-25 ... 55 °C (-13 ... 131 °F)
Relative humidity	
Operation	5 ... 95 %
Storage	5 ... 95 %
Transport	5 ... 95 %

Approvals	
Certificate of suitability	CCC / CE / EAC / KC / RCM / UL

Subject to change. Calculated values may differ from nameplate ratings. © Copyright Siemens