SIEMENS

Data sheet 6ES7193-7AB00-0AA0



Figure similar

SIMATIC, terminal module TM-IM/IM for ET200iSP, for holding two IM152-1 units, in redundant operation, incl. power bus termination module, Ex eb [ia Ga/ib] IIC T4 Gb, Ex eb [ia IIIC Da] IIC T4 Gb, Ex eb [ia/ib] I Mb

General information	
Product type designation	TM-IM/IM
Installation type/mounting	
Rack mounting	No
Front mounting	Yes
Rail mounting	Yes
Wall mounting/direct mounting	No
Supply voltage	
Type of supply voltage	DC
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
Input current	
At DC, max.	4 A
Output voltage	
Type of output voltage	DC
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
Output current	
At DC, max.	4 A
Hardware configuration	
Slots	
● Number of slots	2
● Plug-in modules, analog I/O	No
● Plug-in modules, digital I/O	No
● Plug-in modules, function modules and technology modules	No
● Plug-in modules, communication modules	No
● Plug-in modules, CPUs	Yes
● Plug-in modules, others	Yes
Standards, approvals, certificates	
CE mark	CE 0344
UKCA mark	DEKRA 21UKEX0032 Importer UK: Siemens plc Manchester M20 2UR
cULus	LISTED E334384
FM approval	CLASSIFIED 3025852
Suitable for safety functions	Yes
INMETRO certificate	UL-BR 12.0077
reference designation according to IEC 81346-2 (2009)	XX
Use in hazardous areas	

Subject to change without notice
© Copyright Siemens

● ATEX marking	II 2 G (1) G Ex eb [ia Ga/ib] IIC T4 Gb II 2 G (1) D Ex eb [ia IIIC Da] IIC T4 Gb I M2 Ex eb [ia/ib] I Mb
● ATEX certificate	KEMA 04 ATEX 2242
● IECEx	IECEx KEM 05.0003
● CCC Ex	2020322310002881
● Explosion protection category for gas	ATEX gas explosion protection, Zone 1
● Explosion protection category for dust	ATEX dust explosion protection, Zone 21 always install in corresponding enclosure
● associated equipment (Ex ia)	Yes
● associated equipment (Ex ib)	Yes
Marine approval	
● Germanischer Lloyd (GL)	Yes
● American Bureau of Shipping (ABS)	Yes
● Bureau Veritas (BV)	Yes
● Det Norske Veritas (DNV)	Yes
Dimensions	
Width	60 mm
Height	190 mm
Depth	52 mm
Weights	
Weight, approx.	195 g

Classifications

	Version	Classification
eClass	16	27-24-26-03
eClass	14	27-24-26-03
eClass	12	27-24-26-03
eClass	9.1	27-24-26-03
eClass	9	27-24-26-03
eClass	8	27-24-26-03
eClass	7.1	27-24-26-03
eClass	6	27-24-26-03
ETIM	10	EC001598
ETIM	9	EC001598
ETIM	8	EC001598
ETIM	7	EC001598
IDEA	4	3560
UNSPSC	15	32-15-17-04

Approvals / Certificates

General Product Approval

Miscellaneous

China RoHS

General Product Approval	For use in hazardous locations				
Manufacturer Declaration	ATEX	IECEx	FM	IECEx	Miscellaneous

For use in hazardous locations

Subject to change without notice
© Copyright Siemens

CCC-Ex

Miscellaneous

For use in hazardous locations	Maritime application

Environment

last modified: 4/28/2025

Subject to change without notice
© Copyright Siemens