SIEMENS

Data sheet 6AG1507-0RA00-7AB0



Figure similar

SIPLUS S7-1500 PS 1507 60W 120/AC 230V/DC based on 6ES7507-0RA00-0AB0 with conformal coating, -40…+70 °C, start up -25 °C, system power supply supplies the backplane bus of the S7-1500 with operating voltage

General information	
Product type designation	PS 60 W 120/230 V AC/DC
based on	6ES7507-0RA00-0AB0
Engineering with	
● STEP 7 TIA Portal configurable/integrated from version	see entry ID: 109746275
Supply voltage	
Rated value (DC)	120 V / 230 V
permissible range, lower limit (DC)	88 V
permissible range, upper limit (DC)	300 V
Rated value (AC)	120 V / 230 V
permissible range, lower limit (AC)	85 V
permissible range, upper limit (AC)	264 V
Short-circuit protection	Yes
Line frequency	
● Rated value 50 Hz	Yes
● permissible range, lower limit	47 Hz
● permissible range, upper limit	63 Hz
Mains buffering	
● Mains/voltage failure stored energy time	20 ms
Input current	
Rated value at 120 V DC	0.6 A
Rated value at 230 V DC	0.3 A
Rated value at 120 V AC	0.6 A
Rated value at 230 V AC	0.34 A
Power	
Infeed power to the backplane bus	60 W; > +60 °C max. power input 30 W
Power loss	
Power loss at nominal rating conditions	12 W
Interrupts/diagnostics/status information	
Status indicator	Yes
Potential separation	
primary/secondary	Yes
Isolation	
Isolation tested with	2 500 V DC/2 s (routine test)
EMC	
Interference immunity against voltage surge	
● Interference immunity on supply lines acc. to IEC 61000-4-5	Yes; ±1 kV (acc. to IEC 61000-4-5; 1995; surge symm.), ±2 kV (acc. to IEC 61000-4-5; 1995; surge asymm.), no external protective circuit required

Subject to change without notice
© Copyright Siemens

Degree and class of protection	
IP degree of protection	IP20
Equipment protection class	I, with protective conductor
Ambient conditions	
Ambient temperature during operation	
● min.	-40 °C; = Tmin (incl. condensation/frost); start-up @ -25 °C
● max.	70 °C; = Tmax; for vertical mounting position Tmax = +40 °C
Ambient temperature during storage/transportation	
● min.	-40 °C
● max.	70 °C
Altitude during operation relating to sea level	
● Installation altitude above sea level, max.	2 000 m
● Ambient air temperature-barometric pressure-altitude	Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m)
Relative humidity	
● With condensation, tested in accordance with IEC 60068-2-38, max.	100 %; RH incl. condensation/frost (no commissioning under condensation conditions)
Resistance	
Coolants and lubricants	
— Resistant to commercially available coolants and lubricants	Yes; Incl. diesel and oil droplets in the air
Use in stationary industrial systems	
— to biologically active substances according to EN 60721-3-3	Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request
— to chemically active substances according to EN 60721-3-3	Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
— to mechanically active substances according to EN 60721-3-3	Yes; Class 3S4 incl. sand, dust, *
Use on ships/at sea	
— to biologically active substances according to EN 60721-3-6	Yes; Class 6B2 mold and fungal spores (excluding fauna); Class 6B3 on request
— to chemically active substances according to EN 60721-3-6	Yes; Class 6C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
— to mechanically active substances according to EN 60721-3-6	Yes; Class 6S3 incl. sand, dust; *
Usage in industrial process technology	
— Against chemically active substances acc. to EN 60654-4	Yes; Class 3 (excluding trichlorethylene)
— Environmental conditions for process, measuring and control systems acc. to ANSI/ISA-71.04	Yes; Level GX group A/B (excluding trichlorethylene; harmful gas concentrations up to the limits of EN 60721-3-3 class 3C4 permissible); level LC3 (salt spray) and level LB3 (oil)
Remark	
— Note regarding classification of environmental conditions acc. to EN 60721, EN 60654-4 and ANSI/ISA-71.04	* The supplied plug covers must remain in place over the unused interfaces during operation!
Conformal coating	
● Coatings for printed circuit board assemblies acc. to EN 61086	Yes; Class 2 for high reliability
● Protection against fouling acc. to EN 60664-3	Yes; Type 1 protection
● Military testing according to MIL-I-46058C, Amendment 7	Yes; Discoloration of coating possible during service life
● Qualification and Performance of Electrical Insulating Compound for Printed Board Assemblies according to IPC-CC-830A	Yes; Conformal coating, Class A
Dimensions	
Width	70 mm
Height	147 mm
Depth	129 mm
Weights	
Weight, approx.	600 g

Classifications

	Version	Classification
eClass	16	27-24-22-09
eClass	14	27-24-22-09

Subject to change without notice
© Copyright Siemens

eClass	12	27-24-22-09
eClass	9.1	27-24-22-09
eClass	9	27-24-22-09
eClass	8	27-24-22-09
eClass	7.1	27-24-22-09
eClass	6	27-24-22-09
ETIM	10	EC000599
ETIM	9	EC000599
ETIM	8	EC000599
ETIM	7	EC000599
IDEA	4	3575
UNSPSC	15	32-15-17-06

Approvals / Certificates

General Product Approval

Manufacturer Declaration

China RoHS

General Product Approval

China RoHS

EMV

Maritime application

last modified: 6/17/2025

Subject to change without notice
© Copyright Siemens